

TP-Link Festa F67, Access Point



Model: Festa F67

Manufacturer: TP-LINK

EAN: 8885021370149

Product Code: 304536

R4,039

Produktbeschreibung Der TP-Link Festa F67 Access Point bietet mit bis zu 5,4 Gbit/s WiFi 6- Geschwindigkeit herausragende Leistung für Ihre drahtlose Konnektivität. Er unterstützt bis zu 4804 Mbit/s auf 5 GHz und 574 Mbit/s auf 2,4 GHz. Dank Mesh-Technologie und nahtlosem Roaming genießen Sie stets stabile Verbindungen. Der 2,5 Gigabit PoE-Port und das kompakte Design ermöglichen eine flexible Installation, während das kostenlose zentrale Cloud-Management über die Festa-App oder das Web die Verwaltung erleichtert. Mit Self-Organizing Networking und Zero-Touch Provisioning gestaltet sich die Einrichtung kinderleicht – ganz ohne Techniker. Art.-Nr.: 100101328
Typ: Access Point | EAN: 8885021370149 | Hersteller-Nr.: Festa F67 | Bauform: Deckenmontage | Einsatzbereich: Heimnetzwerke, Business | Anschlüsse: 1x (davon: 1x 100/1000/2500) | WLAN: Wi-Fi 3 (802.11a), Wi-Fi 3 (802.11b), Wi-Fi 3 (802.11g), Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) - (2.4 GHz, 5 GHz, 6 GHz) | Feature: Seamless Roaming, Mesh, Beamforming, Automatic Channel Selection, MU-MIMO, OFDMA, HE320, Band Steering, Load Balance, Airtime Fairness, RADIUS Accounting, Wireless Schedule, Wireless Statistics, Static IP/Dynamic IP, Rate Limit: Based on SSID/Client, Multiple SSIDs: 24(8 on each band), Enable/Disable Wireless Radio, Enable/Disable SSID Broadcast, Guest Network, Transmit Power Control: Adjust Transmit Power on dBm, QoS (WMM) ||

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Captive Portal , Authentication, Access Control, MAC Filter: 4,000, Wireless Isolation Between Clients, OWE, 802.1X Support, VLAN | Weitere Informationen: Zentralisiertes Management durch OMADA SDN, APP support: Festa App, Cloud Access: Free cloud, LED abschaltbar, SNMP: v1, v2c, v3, Lokales/Remote-Systemprotokoll, SSH, Zero-Touch Provisioning | Zubehör: Installationsanleitung, Deckenmontage Kit, Netzteil | Abmessungen: Breite: 220 mm x Höhe: 33,9 mm x Tiefe/Länge: 220 mm | Gewicht: 698 Gramm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950