



**Large Format  
Display DAHUA  
43 3840 x 2160  
pixels 4K Ultra  
HD Native  
aspect ratio  
16:9 LED Flat  
DHI-LM43-F400**

Model: DHI-LM43-F400

Manufacturer: DAHUA

EAN: 6923172561176

Product Code: 309747

**R6,021**

- 4K Ultra-HD resolution
- Suitable for continuous 24/7 operation
- 8ms response time for no motion blur, judder or ghosting
- 1.07B colors, for a realistic and immersive visual experience
- High fidelity digital processing for a brilliant and vivid video
- 178°/178° extra-wide viewing angle for overall viewing performance

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Professional thermal design to extend equipment lifespan

Summary: Dahua Technology DHI-LM43-F400. Display diagonal: 109.2 cm (43"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LED, Response time: 9.5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting. Product colour: Black | Vendor Homepage:

<https://www.dahuasecurity.com/es/products/All-Products/Display--Control/Monitors/Light-Series/LM43-F400> | Backlight type: LED | Contrast ratio (typical): 4000:1 | Display brightness (typical): 300 | Display diagonal: 43 | Display number of colours: 1.073 billion colours | Display resolution: 3840 x 2160 | Display technology: LED | HD type: 4K Ultra HD | Maximum refresh rate: 60 | Native aspect ratio: 16:9 | Response time: 9.5 | Screen shape: Flat | Touchscreen: No | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | Built-in speaker(s): Yes | Number of speakers: 2 | RMS rated power: 16 | Product colour: Black | HDMI: Yes | HDMI ports quantity: 3 | Headphone out: Yes | Headphone outputs: 1 | USB Type-A downstream ports quantity: 1 | Panel mounting interface: 200 x 200 | VESA mounting: Yes | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 54 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): G | Power consumption (standby): 0.5 | Power consumption (typical): 75 | Power supply type: Internal | Operating relative humidity (H-H): 10 - 85 | Operating temperature (T-T): 0 - 40 | Depth (with stand): 86.4 | Depth (without stand): 60.2 | Height (with stand): 566 | Height (without stand): 559.4 | Weight (with stand): 7400 | Width (with stand): 972.5 | Package depth: 130 | Package height: 636 | Package weight: 9500 | Package width: 1060 | Stand included: Yes | Certification: CE/FCC | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/784526/fiches?language=EN> | Energy efficiency class: G | EPREL Registration Number: 784526 | EPREL Version Number: 5 | Model: DHI-LM43-F400 | Model name: DHI-LM43-F400 | Units per Pallet: 0 | Unit Calculated Volume: 0.087/0.1 | Product Net Weight: 7.4 | Unit Calculated Weight: 9.35

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950