



**Switch DAHUA
DH-SG4028LP
26xGigabit
Ethernet
(copper) ports
quantity 2xSFP
module slots
quantity
4xPower over
Ethernet (PoE)
ports quantity
Total Power
over Ethernet
(PoE) budget
240 W
SG4028LP**

Model: SG4028LP

Manufacturer: DAHUA

EAN: 6939554904714

Product Code: 310398

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

R4,613

SG4028LP

28-Port Cloud Managed Desktop Gigabit Switch with 24-Port PoE

Summary: Dahua Technology . Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 2, Installed SFP modules quantity: 2. MAC address table: 8000 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, IEEE.... Power over Ethernet (PoE) | Vendor Homepage: <https://www.dahuasecurity.com/fr/products/All-Products/Transmission/IT-Channel-Products/PoE-Switch/SG4028LP> | Cloud-managed: Yes | Switch layer: L2 | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 2 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP modules quantity: 2 | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3ad/IEEE 802.3af/IEEE 802.3at/IEEE 802.3az/IEEE 802.3bt/IEEE 802.3u/IEEE 802.3x/IEEE 802.3z | Number of VLANs: 32 | Virtual LAN features: Port-based VLAN | VLAN support: Yes | Forwarding rate: 41.66 | Jumbo frames: 15 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4 | Switching capacity: 56 | DHCP features: DHCP client | IP-MAC-Port binding: Yes | Loop protection: Yes | Housing material: Metal | Product colour: Black | Mean time between failures (MTBF): 594334.8 | AC input frequency: 47/63 | AC input voltage: 100 - 240 | Input current: 5 | Power consumption (max): 265 | Power protection features: Over current/Over voltage | Power source: AC | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 24 | Power over Ethernet (PoE) power per port: 30 | Total Power over Ethernet (PoE) budget: 240 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -10 - 55 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 220 | Height: 44 | Weight: 2370 | Width: 440 | Cables included: DC | Quick start guide: Yes | Package depth: 342 | Package height: 90 | Package weight:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

3020 | Package width: 540 | Compliance certificates: CE | Model name: DH-SG4028LP | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.01652 | Unit Calculated Weight: 3.36

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950