

Switch TP-LINK IES210GPP Type L2 PoE+ ports 6 IES210GPP



Model: IES210GPP

Manufacturer: TP-LINK

EAN: 1210002602112

Product Code: 310495

R5,402

**Omada Industrial 10-Port
Gigabit Easy Managed
PoE++ Switch**

Industrial-Grade Protection Built for Harsh Environments

- 10× Gigabit Ports (2× PoE++, 6× PoE+, 2× RJ45/SFP Combo)
- 240W Total PoE Budget
- 40°C to 75°C Operating Temperature
- 12~57VDC 1+1 Redundant Power Input
- Industrial-Grade IP40 Aluminum Casing
- Abundant Functions for CCTV Networking

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Easy Centralised Management

- DIN-Rail & Wall Mounting

- 6× 10/100/1000Mbps RJ45 ports (4× 802.3af/at-compliant PoE+)
- 65W Power Budget, with up to 30W for each PoE port
- Easy to Use: Supports plug-and-play for instant connectivity and simple configuration for additional features
- Centralised Cloud Management via the web or the Omada app
- Up to 250m PoE, QoS, PoE Auto Recovery, and Port Isolation for reliable surveillance networking
- Automatic Loop Prevention, VLAN, and IGMP Snooping
- Fanless design for silent operation
- Durable metal casing and desktop/wall mounting design

Summary: TP-Link Omada 10-Port Gigabit Industrial Easy Managed Switch with 6-Port PoE+ and 2-Port PoE++. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. DC input voltage: 12 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: DIN rail | Vendor Homepage: <https://www.omadanetworks.com/au/business-networking/omada-switch-easy-managed/ies210gpp/#highlights> | Cloud-managed: Yes | Quality of Service (QoS) support: Yes | Switch type: Managed | Web-based management: Yes | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Combo SFP ports quantity: 2 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt | Number of VLANs: 4000 | Port mirroring: Yes | VLAN support: Yes | Forwarding rate: 14.88 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Packet buffer memory: 4000 | Store-and-forward: Yes | Switching capacity: 20 | DHCP features: DHCP client | IGMP snooping: Yes | Loop protection: Yes | Multicast support: Yes | Form factor: DIN rail | LED indicators: Yes | Product colour: Grey | Rack mounting: Yes | DC input voltage: 12 - 57 | Power source: DC | Power over Ethernet (PoE): Yes | Power over Ethernet 4PPoE (PoE++) ports quantity: 2 | Power over Ethernet plus (PoE+) ports quantity: 6 | Total Power over Ethernet (PoE) budget: 240 | Depth: 120 | Height: 60 | Width: 155 | Model: IES210GPP | Model name: IES210GPP | Units per Pallet: 0 | Units per Shipping Box: 4 | Unit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Calculated Volume: 0.004796 | Unit Calculated Weight: 1.66

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950