



## Switch

### TELTONIKA

### SWM281000200

### Switch type

### Managed Switch

### layer L2 24xRJ-

### 45 ports

### SWM281

Model: SWM281

Manufacturer: TELTONIKA

EAN: 4779051846252

Product Code: 310886

## R4,405

### SWM281 Gigabit Ethernet managed switch

The SWM281 is an L2 managed switch with added L3 functionality, tailored for complex networking scenarios. With 24 Gigabit Ethernet ports and 4 dedicated SFP ports, it delivers high-bandwidth performance and reliable fibre optic communication for large-scale deployments. With support of PROFINET & other industrial protocols, this enterprise-grade 24-port switch ensures smooth integration into automated environments.

Summary: Teltonika SWM281. Switch type: Managed, Switch layer: L2+. Basic switching RJ-45

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 24. MAC address table: 8 entries, Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. Rack mounting | Vendor Homepage: <https://www.teltonika-networks.com/products/ethernet-switches/swm281> | Cloud-managed: Yes | Switch layer: L2+ | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 24 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP module slots quantity: 4 | 10G support: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 10,100,1000 | IP routing: Yes | Networking standards: IEEE 802.3ab/IEEE 802.3az/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Port mirroring: Yes | Rate limiting: Yes | Forwarding rate: 83.33 | Jumbo frames: 10000 | Jumbo frames support: Yes | MAC address table: 8 | Packet buffer memory: 0.512 | Switching capacity: 56 | DHCP features: DHCP client/DHCP server | International Protection (IP) code: IP30 | LED indicators: Yes | Product colour: Black | Rack mounting: Yes | Reset button: Yes | Flash memory: 16 | Internal memory: 128 | Memory type: DDR3-SDRAM | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 20 | Power source: AC | Power supply included: No | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): 0 - 50 | Depth: 234 | Height: 44 | Weight: 1853 | Width: 483 | Certification: CE, UKCA, CB, RCM, FCC, IC | Model: SWM281 | Model name: SWM281 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.01742 | Unit Calculated Weight: 2.16

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950