

Switch

TELTONIKA

TSW212000000

TSW212



Model: TSW212

Manufacturer: TELTONIKA

EAN: 4779051841370

Product Code: 310890

R2,711

MANAGED ETHERNET SWITCH

TSW212 is an L2 managed Ethernet switch with additional L3 features, like DHCPv6 client support and static IPv6 routing. This switch supports protocols, including EtherNet/IP, PROFINET, and MRP, and has 8 Gigabit Ethernet ports and 2 SFP ports to ensure robust long-range fibre optic communication.

Summary: Teltonika TSW212. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 8000 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.1Q, IEEE 802.1p, IEEE 802.3az | Vendor Homepage: <https://teltonika-networks.com/products/ethernet-switches/tsw212> | Quality of Service (QoS) support: Yes | Switch layer: L2 | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP module slots quantity: 2 | 10G support: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 10,100,1000 | IP routing: Yes | Networking standards: IEEE 802.1p/IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

802.1Q/IEEE 802.3az | Port mirroring: Yes | VLAN support: Yes | Jumbo frames: 10000 | Jumbo frames support: Yes | MAC address table: 8000 | Switching capacity: 20 | DHCP features: DHCP client/DHCP server | Queue scheduling algorithms: Weighted Round Robin (WRR)/WFQ/WFQ+SP | Security algorithms: SNMPv2/SNMPv3 | International Protection (IP) code: IP30 | LED indicators: LAN/Power | Product colour: Black | Reset button: Yes | Flash memory: 16 | Internal memory: 128 | Memory type: DDR3-SDRAM | Power consumption (max): 6 | Power source: DC | Power supply included: No | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 122.2 | Height: 44.2 | Weight: 615 | Width: 132 | Model: TSW212 | Model name: TSW212000000 | Units per Pallet: 0 | Units per Shipping Box: 16 | Unit Calculated Volume: 0.001455 | Unit Calculated Weight: 0.675

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950