



## Switch

### TELTONIKA

#### 4xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Yes TSW304

Model: TSW304

Manufacturer: TELTONIKA

EAN: 4779051840144

Product Code: 310893

## R1,706

### DIN RAIL SWITCH

TSW304 is the tiniest switch in the Teltonika Networks portfolio, made with the industrial application scenarios in mind. This ultra-small device comes with an integrated DIN rail mounting option and will easily find its place in any server cabinet. Durable design and shock-resistant casing make it perfect for even the most challenging industrial environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

## **MOUNTING**

Integrated DIN rail bracket and surface mounting options

## **COMPACT**

102 x 25 x 81.5 mm

## **GIGABIT ETHERNET**

4 x Gigabit Ethernet with speeds of up to 1000 Mbps

## **7-57 V**

Wide range of supported power supply voltages

Summary: Teltonika TSW304. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 2000 entries, Switching capacity: 8 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3az, IEEE 802.3u. DC input voltage: 7 - 57 V. Power over Ethernet (PoE). Wall mountable | Vendor Homepage: <https://teltonika-networks.com/products/switches/tsw304> | Basic switching RJ-45 Ethernet ports quantity: 4 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: No | Auto MDI/MDI-X: Yes | Ethernet LAN data rates: 10,100,1000 | Networking standards: IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2000 | Packet buffer memory: 0.128 | Switching capacity: 8 | DIN rail mounting: Yes | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: Power/Status | Product colour: Black | Wall mountable: Yes | DC input voltage: 7 - 57 | Input voltage: 9 - 40 | Power consumption (max): 1.44 | Power consumption (typical): 0.26 | Power source: AC/DC | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 81.5 | Height: 25 | Weight: 210 | Width: 102 | Certification: CE, REACH, RoHS, WEEE, UKCA, FCC, IC, CB, RCM | Model: TSW304 | Model name: TSW304 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.00033 | Unit Calculated Weight: 0.23

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950