

WRL ACCESS POINT/TAP100 TELTONIKA



Model: TAP100

Manufacturer: TELTONIKA

EAN: 4779051840182

Product Code: 310897

R853

TAP100 is the first-ever Teltonika Networks Access Point, perfect for strengthening Wi-Fi coverage in small enterprise and commercial spaces. This PoE-in access point can be powered by active PoE devices via its RJ45 port and was designed with simplicity and ease of installation in mind

- POE-IN - Can be powered by PoE devices via RJ45 port
- SLEEK DESIGN - UV-stabilized plastic housing that blends in with its environment
- EASY INSTALLATION - Integrated mounting bracket for easy ceiling setup
- RMS MANAGEMENT - Free access to RMS Management for 24 months

Summary: Teltonika · Accesspoint· TAP100· 2x1· Wi-Fi 4· 300Mbit· 1x 10/100· 15W PoE - Access Point - 0,1 Gbps. 2.4 GHz, Maximum data transfer rate: 300 Mbit/s. Security algorithms: AES-CCMP, TKIP, WPA-PSK, WPA2-EAP, WPA2-PSK, WPA3-EAP, WPA3-SAE. Ethernet LAN data rates: 10,100 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 2 W | Vendor Homepage: <https://teltonika-networks.com/products/access-points/tap100> | 2.4 GHz: Yes | 5 GHz: No | 6 GHz: No | Cabling technology: 10/100Base-T(X) | Ethernet LAN data rates: 10/100 | Maximum

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

data transfer rate: 300 | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.11r/IEEE 802.3/IEEE 802.3az/IEEE 802.3u | VLAN support: Yes | Wi-Fi roaming: Yes | MAC address filtering: Yes | Security algorithms: AES-CCMP/TKIP/WPA2-EAP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-PSK | Firmware upgradeable: Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 1 | WAN connection: Ethernet (RJ-45) | DC voltage range: 44 - 57 | Power consumption (max): 2 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Active PoE | Housing material: Plastic | International Protection (IP) code: IP30 | LED indicators: Power | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | Antenna type: Internal | Built-in processor: Yes | Flash memory: 16 | Internal memory: 64 | Processor frequency: 580 | Certification: IEC 62368-1:2018 EN IEC 62368-1:2020+A11:2020 EN IEC 62311:2020 EN 300 328 V2.2.2 CE, UKCA, CB, FCC, IC, WEEE | Depth: 30 | Height: 158 | Weight: 190 | Width: 158 | Mounting kit: Yes | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Model: TAP100 | Model name: TAP100001000 | Units per Pallet: 0 | Units per Shipping Box: 18 | Unit Calculated Volume: 0.001357 | Unit Calculated Weight: 0.243

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950