

WRL ACCESS POINT/TAP200 TELTONIKA



Model: TAP200

Manufacturer: TELTONIKA

EAN: 4779051840199

Product Code: 310918

R1,205

Wi-Fi 5 ACCESS POINT

Equipped with dual-band technology, fast roaming, and an RJ45 port with PoE-in functionality, the Teltonika Networks TAP200 is a Wi-Fi 5 wireless access point designed to enhance Wi-Fi coverage in medium-density spaces where high network performance is essential. The TAP200 features an integrated mounting bracket for quick and easy installation, and a sleek design to seamlessly blend into retail, enterprise, or any other environment.

- WI-FI 5 Wave-2 802.11 b/g/n/ac Dual Band Wi-Fi
- RJ45 & POE-IN Supporting speeds of up to 1000 Mbps and PoE-in functionality
- RESILIENT & EASY TO INSTALL UV-stabilised housing for lasting colour with a mounting bracket for quick setup
- RMS MANAGEMENT Free RMS Management access for 24 months

Summary: Teltonika TAP200. 2.4 GHz, 5 GHz, Maximum data transfer rate: 867 Mbit/s. Security algorithms: AES-CCMP, EAP-TLS, HTTPS, OWE, PEAP, SSH, TKIP, WPA-EAP, WPA-PSK, WPA2-EAP,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

WPA2-PSK, WPA3-EAP,.... Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE).
Product colour: White | Vendor Homepage: <https://teltonika-networks.com/products/access-points/tap200> | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Cabling technology: 10/100/1000Base-T(X) | Ethernet LAN data rates: 10/100/1000 | Maximum data transfer rate: 867 | Maximum data transfer rate (2.4 GHz): 300 | MIMO: Yes | MIMO type: Multi User MIMO | Networking standards: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.11r/IEEE 802.3/IEEE 802.3az/IEEE 802.3u | Number of users: 100 | VLAN support: Yes | Wi-Fi roaming: Yes | MAC address filtering: Yes | Security algorithms: AES-CCMP/EAP-TLS/HTTPS/OWE/PEAP/SSH/TKIP/WPA2-EAP/WPA2-PSK/WPA3-EAP/WPA3-SAE/WPA-EAP/WPA-PSK | Supported network protocols: TCP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, SSL v3, TLS, ARP, SSH | Command-line interface (CLI): Yes | Firmware upgradeable: Yes | Web-based management: Yes | Ethernet LAN (RJ-45) ports: 1 | WAN connection: Ethernet (RJ-45) | DC voltage range: 44 - 57 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Active PoE | Housing material: Plastic | International Protection (IP) code: IP30 | LED indicators: Power | Placement: Ceiling,Wall | Product colour: White | Reset button: Yes | Antenna type: Internal | Antennas quantity: 2 | Built-in processor: Yes | Flash memory: 16 | Internal memory: 256 | Operating system installed: RutOS | Processor frequency: 880 | Certification: CE, UKCA, FCC, IC, RCM, CB, EAC, UCRF, WEEE | Depth: 158 | Height: 30 | Weight: 190 | Width: 158 | Mounting kit: Yes | Quantity per pack: 1 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Model: TAP200 | Model name: TAP200000000 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0009874 | Unit Calculated Weight: 0.23

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950