
Switch TP-LINK
Switch type
Managed Rack
mounting Yes
4xRJ-45 ports RJ-
45 Ports Type
Gigabit Ethernet
(10/100/1000)
1xCombo SFP
ports quantity
1xSFP module
slots quantity
Power over
Ethernet (PoE)
Yes 3xPower
over Ethernet
plus (PoE+)
ports quantity
1xPower over
Ethernet 4PPoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

(PoE++) ports quantity Total Power over Ethernet (PoE) budget 120 W IES206GPP



Model: IES206GPP

Manufacturer: TP-LINK

EAN: 1210002602051

Product Code: 310965

R4,873

Industrial-Grade Protection Built for Harsh Environments

Enhanced Networking Stability and Security

Easy Operation and Maintenance with Omada's Free Cloud Management

- 4× Gigabit RJ45 Ports (1× PoE++, 3× PoE+)
- 1× Gigabit Combo RJ45/SFP Slot, 1× Gigabit SFP Slot
- 120W Power Budget* with up to 60W for PoE++ Port
- Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
- Abundant Features: Up to 820ft (250m) PoE,** VLAN, QoS, and STP/RSTP
- Centralized Cloud Management via the Web or Omada App

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design

Summary: TP-Link IES206GPP. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 8000 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE.... DC input voltage: 12 - 57 V. Power over Ethernet (PoE). Wall mountable, Rack mounting | Vendor Homepage: <https://www.omadanetworks.com/nordic/business-networking/omada-switch-industrial/ies206gpp/> | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 4 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Combo SFP ports quantity: 1 | SFP module slots quantity: 1 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1D/IEEE 802.1p/IEEE 802.1Q/IEEE 802.1w/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3x | Port mirroring: Yes | Spanning tree protocol: Yes | Forwarding rate: 8.93 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Store-and-forward: Yes | Switching capacity: 12 | DHCP features: DHCP client | IGMP snooping: Yes | Multicast support: Yes | DIN rail mounting: Yes | Product colour: Black | Rack mounting: Yes | Wall mountable: Yes | Fanless: Yes | DC input voltage: 12 - 57 | Power source: DC/PoE | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) type supported: PoE+/PoE++ (4PPoE) | Power over Ethernet 4PPoE (PoE++) ports quantity: 1 | Power over Ethernet plus (PoE+) ports quantity: 3 | Total Power over Ethernet (PoE) budget: 120 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -40 - 75 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 85 | Depth: 120 | Height: 60 | Width: 155 | Quick start guide: Yes | Certification: FCC, CE, RoHS | Model: IES206GPP | Units per Pallet: 0 | Units per Shipping Box: 4 | Unit Calculated Volume: 0.00473 | Unit Calculated Weight: 1.4875

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950