

## Switch DAHUA SF1008L-EUR SF1008L-EUR



Model: DH-SF1008L

Manufacturer: DAHUA

EAN: 6923172583536

Product Code: 311005

## R215

The Device is a layer-2 commercial switch. It has a high-performance switching engine and a large buffer memory to ensure smooth video stream transmission. With a plastic and fanless design, the device provides a more cost-effective option for customers. The Device is an unmanaged switch, so it does not need to be configured through web interface, which simplifies installation.

### Robust Design

Built to last, the architecture of the switch makes it highly reliable, operating with high-efficiency non-stop.

### Plug and Play

Hassle-free, it does not require any configuration. Simply use after it is powered on.

### Optimized Performance

All ports can transmit streams at high speeds without delay.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

## Easy Installation

Both desktop and wall mount installation are supported, making it suitable for a wide variety of scenarios.

- > Supports five 10/100 Mbps adaptive ports
- > Small and light, it is easy to carry and has multiple chips embedded in it
- > Easy to operate

Summary: Dahua Technology PoE DH-SF1008L. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 8. MAC address table: 2000 entries, Switching capacity: 1.6 Gbit/s. DC input voltage: 5 V. Power over Ethernet (PoE). Form factor: Desktop | Vendor Homepage: <https://transmission.dahuasecurity.com/en/product-list/Home/SOHOSwitches/PlasticSwitch/SF1008L> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 8 | Uplink ports quantity: 1 | 10G support: No | Cable types supported: Cat5e/Cat6 | Copper ethernet cabling technology: 10BASE-T | Ethernet LAN data rates: 10,100 | Flow control support: Yes | Forwarding rate: 0.744 | MAC address table: 2000 | Packet buffer memory: 0.768 | Switching capacity: 1.6 | Form factor: Desktop | LED indicators: Yes | Product colour: Light grey | Rack mounting: No | Mean time between failures (MTBF): 952.5 | DC input voltage: 5 | Input current: 1 | Power consumption (max): 0.5 | Power consumption (typical): 0.1 | Power source: DC/PoE | Power over Ethernet (PoE): Yes | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): 0 - 45 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 70 | Depth: 62.4 | Height: 24 | Weight: 160 | Width: 132.9 | Package depth: 90 | Package height: 63.5 | Package weight: 290 | Package width: 138 | Model name: DH-SF1008L | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.0008222 | Unit Calculated Weight: 0.21

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950