



**Switch**  
**TELTONIKA**  
**Switch type**  
**Unmanaged**  
**Form factor DIN**  
**rail 5xRJ-45**  
**ports RJ-45**  
**Ports Type Fast**  
**Ethernet**  
**(10/100) 5xFast**  
**Ethernet**  
**(copper) ports**  
**quantity**  
**TSF010000000**

Model: TSF010000000

Manufacturer: TELTONIKA

EAN: 4779051841356

Product Code: 311120

---

**R908**

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

The TSF010 is an unmanaged Ethernet switch featuring a flat design and integrated DIN rail mounting for plug-and-play deployment in industrial cabinet applications. This Ethernet switch is compact and lightweight, measuring 113 x 28 x 50 mm and weighing only 142 g. Its 3-pin power input and 7-57 VDC voltage range make it a flexible unmanaged switch tailor-made for industrial use. The TSF010 is equipped with five 10/100 Mbps RJ45 ports for reliable connectivity.

- 3-PIN POWER INPUT
- Flexible and tailor-made for industrial use
- FLAT & COMPACT
- Flat and compact design weighing only 142 g
- INTEGRATED DIN RAIL BRACKET
- Easy mounting for plug-and-play deployment
- 7-57 VDC
- Suitable voltage range for industrial applications

Summary: Teltonika NETWORKS TSF010 Flat Ethernet Switch. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100), Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. MAC address table: 2048 entries, Switching capacity: 10 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Form factor: DIN rail | Vendor Homepage: <https://teltonika-networks.com/products/ethernet-switches/TSF010/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 5 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Fast Ethernet (copper) ports quantity: 5 | 10G support: No | Auto MDI/MDI-X: Yes | Full duplex: Yes | Networking standards: IEEE 802.3/IEEE 802.3ab/IEEE 802.3u/IEEE 802.3x | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2048 | Switching capacity: 10 | DIN rail mounting: Yes | Form factor: DIN rail | Housing material: Aluminium | International Protection (IP) code: IP30 | Product colour: Black | Rack mounting: No | Stackable: No | Input voltage: 7 - 57 | Power consumption (max): 1.5 | Power consumption (typical): 1 | Power source: DC | Power supply included: No | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 50 | Height: 28 | Weight: 142 | Width: 113 | Units per Pallet: 0 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.000237 | Unit Calculated Weight: 0.15

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950