

**LCD Monitor**  
**AOC 27 2560 x**  
**1440 pixels**  
**Quad HD Native**  
**aspect ratio**  
**16:9 LED Flat**  
**Q27E4CV**



Model: Q27E4CV

Manufacturer: AOC

EAN: 4038986182829

Product Code: 311360

**R5,463**

### **Optimize your workflow with the Q27E4CV 27" QHD monitor**

The Q27E4CV features a 27" QHD display with a 120Hz refresh rate for smooth, clear visuals. It includes a Height Adjustable Stand for ergonomic comfort and hardware-based anti-blue light to reduce eye strain. With built-in docking and 90W Power Delivery, it simplifies connectivity and keeps your workspace efficient.

Summary: AOC E4 Q27E4CV. Display diagonal: 68.6 cm (27"), Display resolution: 2560 x 1440 pixels, HD type: Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black | Vendor Homepage: <https://eu.aoc.com/> | Anti-glare screen: Yes | Backlight type: W-LED | Contrast ratio (dynamic): 20000000:1 | Contrast ratio (typical): 1500:1 | Digital horizontal frequency: 30 - 230 | Digital vertical frequency: 48 - 120 | Display brightness (typical): 350 | Display diagonal: 27 | Display diagonal (metric): 68.6 | Display number of colours: 16.7 million colours | Display resolution: 2560 x 1440 | Display technology: LED | Haze rate: 25 | HD type: Quad HD | High Dynamic Range (HDR) supported: Yes | LED backlight: Yes | Maximum refresh rate: 120 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 109 | Pixel pitch: 0.2331 x 0.2331 | Response time: 4 | Response time measurement type: GTG (Gray to Gray) | Screen shape: Flat | sRGB coverage (typical): 99 | Surface hardness: 3H | Touchscreen: No | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | Flicker-free technology: Yes | Low Blue Light technology: Yes | VESA Adaptive Sync support: Yes | Built-in camera: No | Built-in speaker(s): Yes | Number of speakers: 2 | RMS rated power: 4 | Detachable stand: Yes | Front bezel colour: Black | Market positioning: Office | Product colour: Black | Audio output: Yes | Built-in USB hub: Yes | DisplayPort out quantity: 1 | DisplayPort out version: 1.2 | DisplayPort version: 1.2 | DisplayPorts quantity: 1 | HDCP: Yes | HDCP version: 1.4/2.2 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone out: Yes | Headphone outputs: 1 | Number of USB Type-C upstream ports quantity: 1 | USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1) | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 90 | USB Type-A downstream ports quantity: 4 | USB Type-C DisplayPort Alternate Mode: Yes | Ethernet LAN: Yes | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Cable management: Yes | Height adjustment: Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Swivel angle range: -180 - 180 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 30 | VESA mounting: Yes | Energy consumption (HDR) per 1000 hours: 16 | Energy consumption (SDR) per 1000 hours: 16 | Energy efficiency class (HDR): D | Energy efficiency class (SDR): D | Energy efficiency scale: A to G | Power consumption (off): 0.3 | Power consumption (standby): 0.3 | Power consumption (typical): 23.25 | Power supply type: Internal | Weight (with stand): 6150 | Weight (without stand): 4140 | Width (with stand): 616 | Width (without stand): 616 | Package depth: 139 | Package height: 480 | Package weight: 9050 | Package width: 730 | Cables included: AC/DisplayPort/HDMI/USB Type-C | DisplayPort cable length: 1.8 | HDMI cable length: 1.8 | Power cable length: 1.8 | Doesn't contain: Mercury/PVC/BFR | Sustainability certificates: EPEAT Gold/TCO | Certification: WEEE,REACH compliant,RoHs compliant,CB,TUV-GS-Mark,TUV Ergo,EAC,FCC | Compliance certificates: CE | Local dimming: Yes | Mean time between failures (MTBF): 70000 | Warranty period: 5 | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2383670/fiches?language=EN> | Energy efficiency class: D |

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](https://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950

EPREL Registration Number: 2383670 | EPREL Version Number: 1 | Units per Pallet: 0 | Unit  
Calculated Volume: 0.04727 | Product Net Weight: 6.15 | Unit Calculated Weight: 9

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950