

DISPLAY LCD 65/65UL5Q-E LG



Model: 65UL5Q-E

Manufacturer: LG

EAN: 8806096602164

Product Code: 311425

R20,781

Superb Picture Quality with Ultra HD Resolution

The UL5Q-E series, with UHD resolution, enhances the realism of colors and details in the content. Its wide viewing angle offers clear visuals, while its 500-nit brightness vividly showcases the content.

High-Performance with LG webOS 6.1

LG webOS 6.1 is available on the UL5Q-E series for smooth execution of multiple tasks. The LG webOS smart signage platform enhances user convenience with an intuitive GUI.

Even Bezel Design

The UL5Q-E series features even bezels, enhancing the aesthetic appeal of various spaces. These uniform bezels not only facilitate easy installation but also transform standard displays into elegant focal points.

Adaptive Viewing Experience

Experience the flexibility with the UL5Q-E series' up/down tilt capability. Whether mounted high or low, the display can be adjusted to eye level, offering viewer engagement regardless of installation

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

height. This versatility not only enhances spatial efficiency but also provides visual comfort, delivering clear information from various viewing angles.

Engineered for 24/7 Operation

Built for environments that never sleep, the UL5Q-E series features panel technology that enables 24/7 operation.

Built-In Brightness Sensor

The UL5Q-E series' front-mounted brightness sensor automatically adjusts brightness to match various lighting conditions, optimizing viewing quality and energy efficiency without manual intervention. This adaptive feature offers consistent display performance while also supporting power optimization, delivering a visual experience that dynamically responds to environmental changes.

Advanced Security Architecture

The UL5Q-E series incorporates LG's Enhanced Kernel Protection (EKP) technology, safeguarding critical data from unauthorized access and potential security threats. This commitment to information security is validated by the ISO/ IEC 15408 Common Criteria EAL2 certification, providing businesses with the confidence that their sensitive content and operations remain protected in today's challenging security landscape.

Remote Monitoring and Control

This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anytime, anywhere from their mobile phone & PC in a network-accessible environment, with access to both current and past data. It allows the user to monitor the unit, make adjustments, and control the unit remotely in real time.

EPEAT Registered

The Electronic Product Environmental Assessment Tool (EPEAT) is a method for several layers of customers to evaluate the effect of a product on the environment. UL5Q-E series is an EPEAT Bronze-certified* display which means that it meets all the required criteria in the Computers and Displays category.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

LG ConnectedCare

Maintenance is easy and fast with the optional LG ConnectedCare* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, supporting the stable operation of clients' businesses. Long Description: LG 65UL5Q-E. Product design: Digital signage flat panel. Display diagonal: 165.1 cm (65"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 500 cd/m², HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 24/7. Operating system installed: WebOS. Product colour: Black | Vendor Homepage: <https://www.lg.com/global/business/commercial-display/digital-signage/standard/65ul5q-e/> | Bullet Points:

- Resolution : 3,840 × 2,160 (UHD)
- Brightness : 500 nit (Typ.)
- 24Hr Usage Scene (24 Hours / 7 Days)
- Face Up/Down with Tilt Support
- Even Bezel
- High-Performance with webOS 6.1

| Purpose: Commercial | HDMI ports quantity: 3 | HDMI version: 2.2/1.4 | USB port: Yes | Product design: Digital signage flat panel | Ethernet LAN: Yes | Placement supported: Indoor | Display diagonal: 65 | Ethernet LAN (RJ-45) ports: 1 | Display technology: LED | Wi-Fi: Yes | Panel type: ADS | Display resolution: 3840 x 2160 | Orientation: Horizontal/Vertical | Display brightness: 500 | HD type: 4K Ultra HD | Product colour: Black | Touchscreen: No | Native aspect ratio: 16:9 | Response time: 8 | Model name: 65UL5Q-E | Contrast ratio (typical): 1200:1 | Contrast ratio (dynamic): 1000000:1 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | Display number of colours: 1.07 billion colours | VESA mounting: Yes | Built-in speaker(s): Yes | Panel mounting interface: 200 x 200 | Power consumption (typical): 155 | RS-232C: Yes | Power consumption (standby): 0.5 | Power consumption (off): 0.5 | Power consumption (economy mode): 0.5 | Internal memory: 8 | Operating system installed: WebOS | Operating system version: 6.1 | Energy efficiency class (SDR): G | Energy efficiency class (HDR): Not available | Display width: 1452.9 | Energy consumption (SDR) per 1000 hours: 154 | Colour saturation: 80 | Display depth: 59.7 | Display height: 829.2 | Display weight: 16500 | Gyroscope: Yes | Temperature sensor: Yes | AC input voltage: 100 - 240 | AC input frequency: 50/60 | On Screen Display (OSD) languages: Arabic/Czech/Danish/Dutch/English/Finnish/French/German/Greek/Italian/Japanese/Korean/Norwegian/Polish/Chinese/Spanish/Swedish/Traditional Chinese/Turkish | Operating temperature (T-T): 0 - 40 | Remote control included: Yes | Operating relative humidity (H-H): 10 - 80 | Operating hours (hours/days):

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

24/7 | Bezel width (bottom): 10.7 | Number of built-in speakers: 2 | Bezel width (side): 10.7 | Bezel width (top): 10.7 | Energy efficiency class: G | Bezel colour: Black | Rated lifetime: 30000 | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2417291/fiches?language=EN> | EPREL Version Number: 2 | EPREL Registration Number: 2417291 | Power supply type: Internal | Compliance certificates: CB/CE/Electromagnetic Compatibility (EMC)/Federal Communications Commission (FCC) | Cables included: Power | Web browser: Yes | webRTC support: Yes | RMS rated power: 20 | PC Audio out: Yes | Haze rate: 1 | Native refresh rate: 60 | Package width: 1635 | Package depth: 976 | Package height: 141 | Package weight: 21800 | Units per Pallet: 0 | Unit Calculated Volume: 0.225 | Unit Calculated Weight: 21.8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950