

## DISPLAY LCD 55/55UL3Q-E LG



Model: 55UL3Q-E

Manufacturer: LG

EAN: 8806096497487

Product Code: 311427

# R15,606

### Superb Picture Quality with Ultra HD Resolution

With the resolution of UHD, it makes the color and details of the contents vivid and realistic. In addition, the wide viewing angle provides clear contents.

### High-Performance with LG webOS 6.1

LG webOS 6.1 is available on the UL3Q series for smooth execution of multiple tasks. The LG webOS smart signage platform enhances user convenience with an intuitive GUI\*.

### Easy Installation with Uniform Bezel Design

The UL3Q series features perfectly balanced horizontal and vertical bezels, creating a visually harmonious display solution. Its specialized design simplifies installation in retail environments while delivering a truly immersive viewing experience. The sophisticated, symmetrical bezels enhance the aesthetic appeal of any space, transforming ordinary displays into elegant focal points.

### Adaptive Viewing Experience

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Experience enhanced flexibility with the UL3Q's innovative Face Up/Down tilt support. Whether mounted high or low, each display can be adjusted to better meet viewers at eye level, promoting maximum engagement regardless of installation height. This versatility optimizes both spatial efficiency and visual comfort, delivering clear information from various viewing angles.

### **Remote Monitoring and Control**

This web-based monitoring solution is user-friendly and allows the user to be at ease. It enables the user to have full access anywhere at anytime from their mobile phone & PC under network-accessible environment while having access to both current and past data. It allows the user to monitor the unit, make adjustments and control the unit remotely in real time.

### **Built-In Brightness Sensor**

The UL3Q's front-mounted sensor automatically adjusts brightness to match various lighting conditions, helping to optimize viewing quality and energy efficiency without manual intervention. This adaptive feature helps maintain consistent display performance while supporting power savings, delivering improved visual experience that responds to environmental changes.

### **Advanced Security Architecture**

The UL3Q incorporates LG's Enhanced Kernel Protection (EKP) technology, safeguarding critical data from unauthorized access and potential security threats. This commitment to information security is validated by the ISO/IEC 15408 Common Criteria EAL2 certification, providing businesses with the confidence that their sensitive content and operations remain protected in today's challenging security landscape.

### **Award-Winning Sustainability**

The UL3Q series embodies LG Display's ESG commitment: "Better Life for All." This company-wide dedication to environmental responsibility has earned the prestigious 2025 EcoVadis Platinum medal, placing us among the top 1% of global companies for sustainability excellence.

### **LG ConnectedCare**

Maintenance is easy and fast with the optional LG ConnectedCare\* service, a cloud service solution provided by LG. It remotely manages the status of displays in client workplaces for fault diagnosis and remote-control services, supporting the stable operation of clients' businesses.

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Brightness : 350 nit (Typ.)
- Face Up/Down with Tilt Support
- High-Performance with webOS 6.1
- Enhanced Security
- Sustainability for ESG

Summary: LG 55UL3Q-E. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display technology: LED, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m<sup>2</sup>, HD type: 4K Ultra HD. Wi-Fi. Operating hours (hours/days): 16/7. Product colour: Black | Vendor Homepage: <https://www.lg.com/global/business/digital-signage/lg-55ul3q-e> | Colour saturation: 80 | Contrast ratio (dynamic): 1000000:1 | Contrast ratio (typical): 1200:1 | Display brightness: 350 | Display diagonal: 55 | Display number of colours: 1.07 billion colours | Display resolution: 3840 x 2160 | Display technology: LED | Haze rate: 1 | HD type: 4K Ultra HD | Native aspect ratio: 16:9 | Native refresh rate: 60 | Panel type: ADS | Rated lifetime: 30000 | Response time: 8 | Touchscreen: No | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 3 | HDMI version: 2.2/1.4 | PC Audio out: Yes | RS-232C: Yes | USB port: Yes | Built-in speaker(s): Yes | Number of built-in speakers: 2 | RMS rated power: 20 | Bezel colour: Black | Bezel width (bottom): 10.8 | Bezel width (side): 10.8 | Bezel width (top): 10.8 | Orientation: Horizontal/Vertical | Panel mounting interface: 300 x 300 | Placement supported: Indoor | Product colour: Black | Product design: Digital signage flat panel | VESA mounting: Yes | On Screen Display (OSD) languages:

Arabic/Czech/Danish/Dutch/English/Finnish/French/German/Greek/Italian/Japanese/Korean/Norwegian/Polish/Chinese/Spanish/Swedish/Traditional Chinese/Turkish | Operating hours (hours/days): 16/7 | Web browser: Yes | webRTC support: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): G | Heat generation (max): 525.4697 | Heat generation (typical): 334.39 | Power consumption (economy mode): 0.5 | Power consumption (max): 154 | Power consumption (off): 0.5 | Power consumption (standby): 0.5 | Power consumption (typical): 98 | Internal memory: 8 | Display depth: 58.9 | Display height: 706.7 | Display width: 1234.2 | Package depth: 825 | Package height: 118 | Package weight: 15400 | Package width: 1380 | Cables included: Power | Remote control included: Yes | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Ethernet LAN: Yes | Gyroscope: Yes | LG technologies (AV/TV): Auto Set ID, Booting Logo Image, Control Manager, Fail over, Gapless

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Playback,Group Manager,ISM Method,Local Contents Scheduling,Local Network Sync,No Signal Image,RS232C Sync,SI Server Setting,Setting Data Cloning,Smart Energy Saving,Status Mailing,Video Tag | Temperature sensor: Yes | Wi-Fi: Yes | Compliance certificates: CB/CE/Electromagnetic Compatibility (EMC)/Federal Communications Commission (FCC) | Power supply type: Internal | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2293365/fiches?language=EN> | Energy efficiency class: G | EPREL Registration Number: 2293365 | EPREL Version Number: 2 | Units per Pallet: 0 | Unit Calculated Volume: 0.1343 | Unit Calculated Weight: 15.4

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950