



Mercusys 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router



Model: MB230-4G

Manufacturer: MERCUSYS

EAN: 6957939001827

Product Code: 324111

R1,649

Receiver sensitivity: 11g 6Mbps: -95dBm 11g 54Mbps: -77dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71dBm 11a 6Mbps: -92dBm 11a 54Mbps: -75dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65dBm 11ac VHT80 MCS9: -61dBm | WAN connection type: RJ-45 | Port-based Network Access Control (PNAC): Yes | VoIP protocols: IPv4, IPv6 | Security algorithms: WPA2-PSK | WPS push button: Yes | Universal Plug and Play (UPnP): Yes | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 4G bands supported: 1800 | Networking standards: IEEE 802.11b | Security algorithms: WPA3-SAE | Operating temperature (T-T): 0 - 40 °C | Ethernet WAN: Yes | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Ethernet LAN data rates: 1000 | DSL WAN: No | 4G bands supported: 900 | Ethernet LAN data rates: 100 | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.11a | Quick installation guide: Yes | 4G bands supported: 2600 MHz | 4G bands supported: 850 | Ethernet LAN interface type: Gigabit Ethernet | DC-in jack: Yes | USB port: No | Package type: Box | DMZ support:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | 3G standards: HSPA | System event log: Yes | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | 4G bands supported: 2100 | 4G bands supported: 800 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | WLAN data transfer rate (max): 1200 Mbit/s | 3G standards: UMTS | 4G bands supported: 700 | 4G bands supported: 2300 | Port triggering: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Ethernet LAN (RJ-45) ports: 2 | Firewall: Yes | Operating relative humidity (H-H): 10 - 90% | SIM card type: NanoSIM | Ethernet LAN: Yes | Security algorithms: 64-bit WEP | Networking standards: IEEE 802.11ac | Cabling technology: 10/100/1000Base-T(X) | Wi-Fi standards: 802.11g | Dynamic DNS (DDNS): Yes | Depth: 61 mm | SIM card slot: Yes | Port forwarding: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11b | DHCP server: Yes | Dual SIM support: No | Output voltage: 12 V | Indication light: Yes | Wi-Fi standards: 802.11a | Wi-Fi Multimedia (WMM)/(WME): Yes | Height: 166 mm | Power source type: DC | Width: 95 mm | Product type: Desktop/pole router | Output current: 1 A | 3G/4G USB modem compatibility: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | UMTS bands supported: 2100 MHz | Mobile network generation: 4G | UMTS bands supported: 900 | UMTS bands supported: 850 | Antenna design: Internal

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950