



Duracell MN21 Single-use battery Alkaline



Model: 850

Manufacturer: DURACELL

EAN: 5000394203969

Product Code: 393639

R569

ADVANTAGES AND APPLICATIONS

The DURACELL zinc/potassium hydroxide/manganese dioxide battery system, commonly referred to as alkaline or Alkaline Manganese Dioxide, is now recognized as the premium primary zinc anode battery system. It has been selected for consumer, industrial and military applications where an economical and reliable battery is required.

Its major advantages (compared to the zinc-carbon battery system) are a high energy density; the ability to operate continuously at relatively high discharge rates over a wide temperature range (due to its lower internal resistance); and a shelf life in excess of four years. The cost of the alkaline battery, on a service life basis, is lowest in medium to high drain applications.

CHEMISTRY

The components of the alkaline-manganese battery are a zinc anode, a manganese dioxide cathode, and a highly conductive potassium hydroxide electrolyte.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

CONSTRUCTION

The DURACELL alkaline cell is cylindrical in design. A cutaway view of a representative battery is shown above.

RATED CAPACITY

The DURACELL alkaline battery system is available in standard cylindrical and multicell configurations (34 mAh to 15,000 mAh).

PERFORMANCE CHARACTERISTICS

Voltage

The open circuit voltage ranges from 1.5 to 1.6V, depending on cathode formulation. Typical median operating voltage ranges from 1.3 to 1.1V under moderate discharge conditions.

Discharge Characteristics

Moderately sloping discharge curve.

Energy Density

75 Wh/lb. (163 Wh/kg); 6.5 Wh/in.³ (398 Wh/l).

Effect of Discharge Load and Temperature

Capable of performance at high discharge rates; typical temperature range: -4°F to 130°F (-20°C to 54°C).

Shelf Life

Up to 85% capacity remaining after 4 years of storage at 70°F (21°C).

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950