

NET CAMERA 8+4MP PTZ DOME/SDT4E425-8P-GB-APV1 DAHUA

NET CAMERA 8+4MP PTZ DOME/SDT4E425- 8P-GB-APV1 DAHUA



Model: SDT4E425-8P-GB-APV1

Manufacturer: DAHUA

EAN: 6939554910708

Product Code: 405790

R25,021

8+4MP 25x TiOC Network Panoramic PTZ Camera

- Overview channel: Outputs 180° wide angle splicing image
- Detail channel: 1/2.8"4Megapixel STARVIS™ CMOS
- 25x optical zoom
- Max. 25/30 fps@8M
- IR distance up to 100 m
- Auto tracking 3.0
- Smart tracking
- Perimeter protection
- Active deterrence

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Smart dual light +

Summary: Dahua Technology WizSense SDT4E425-8P-GB-APV1. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Tilt preset speed: 90 °/sec, Tilt manual speed: 0.1 - 90 °/sec, Pan preset speed: 180 °/sec. Sensor type: CMOS. Digital zoom: 16x, Detect distance: 56 m, Observe distance: 24.4 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/PTZ-Cameras/X-Spans-Series/Distribution/SDT4E425-8P-GB-APV1> | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: White | International Protection (IP) code: IP66 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | PTZ control: Yes | PTZ modes: Preset point | Tour recording: Yes | Preset points: Yes | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Remote viewing: Yes | Built-in light: Yes | Camera pan control: Yes | Camera tilt control: Yes | Tilt manual speed: 0.1 - 90 | Tilt preset speed: 90 | Pan manual speed: 0.1 - 180 | Pan preset speed: 180 | Camera shutter type: Electronic | Camera shutter speed: 1 - 1/30000 | Sensor type: CMOS | Digital zoom: 16 | Detect distance: 56 | Observe distance: 24.4 | Recognize distance: 11.2 | Detect distance (tele): 2500 | Detect distance (wide): 100 | Identify distance (tele): 250 | Identify distance (wide): 10 | Observe distance (tele): 1000 | Observe distance (wide): 40 | Recognize distance (tele): 500 | Recognize distance (wide): 20 | Night vision: Yes | Maximum resolution: 4096 x 1860 | Total megapixels: 8 | Frame rate: 30 | Noise reduction: Yes | Noise reduction technology: 2D noise reduction,3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: H265: 51 kbps-13,312 kbps | Bit rate control: Constant Bit Rate (CBR),Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Signal-to-Noise Ratio (SNR): 55 | Built-in microphone: Yes | Ethernet LAN: Yes | Wi-Fi: No | Bluetooth: No | Built-in HDD: No | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 2 | Alarm output channels: 1 | Mirror: Yes | Video motion detection: Yes | Power source type: DC,PoE | DC output voltage: 12 | Width: 194.2 | Depth: 160 | Height: 311 | Weight: 3100 | Number of cameras: 1 | Manual: Yes | Unit Calculated Weight: 5.25 | Product Net Weight: 3.1 | Unit Calculated Volume: 0.03863 | Units per Shipping Box: 2 | Unit Width: 26 | Units per Pallet: 0 | Shipping Box Height: 54.5 | Unit Depth: 49 | Unit Height: 24 | Name: NET CAMERA 8+4MP PTZ DOME/SDT4E425-8P-GB-APV1 DAHUA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950