



NET CAMERA M4218-V DOME/02678- 001 AXIS



Model: 02678-001

Manufacturer: AXIS

EAN: 7331021081536

Product Code: 405907

R15,261

This discreet dome delivers great images in challenging light conditions. With a deep learning processing unit, it offers intelligent analytics based on deep learning on the edge. Plus, Axis Edge Vault safeguards your device.

Great images, every time

Ideal for indoor surveillance applications, AXIS M4218-V delivers great image quality in superior 4K. With a varifocal lens, this affordable camera offers a flexible field of view. Plus, with remote zoom and auto focus capabilities, it ensures sharp high resolution video with great details where needed. Thanks to WDR, it can handle difficult light conditions. Furthermore, Axis Edge Vault provides a hardware-based cybersecurity platform that guarantees the device's integrity and protects it from unauthorized access.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Extended possibilities

AXIS M4218-V offers great possibilities to add value to your camera and extend the functionality of your surveillance system. For instance, with an HDMI port and AXIS Face Detector you can display live video and face detection on a public viewing monitor to help deter theft. Plus, you can add audio or I/O connectivity using AXIS T61 Series. It offers advanced analytics based on deep learning on the edge to deliver valuable metadata facilitating efficient forensic search capabilities in live or recorded video. And AXIS Object Analytics including time in area feature lets you track whenever an object stays in a defined area longer than a user-defined time, for example, to detect loitering.

Small and discreet

Compact and flexible in design, this varifocal dome offers flexible and discreet installation. With a wide range of accessories, it can be installed almost anywhere making it ideal for any location where discreet monitoring is needed. And it can be easily repainted to blend in seamlessly with any environment. This IK08-rated camera is protected against redirection, defocusing, and impact. A smoked dome is available as an accessory to disguise which way the camera is pointing. Furthermore, thanks to its vandal-, impact-, and dust-resistant casing you can be confident it's always safe and secure.

- Great image quality in superior 4K
- Varifocal lens with remote zoom and focus
- WDR for difficult light conditions
- Analytics with deep learning
- HDMI output for public viewing monitors

Summary: Axis 02678-001. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Minimum illumination: 0.24 lx, Angle of rotation: 105°, Lens viewing angle, horizontal: 93 - 47°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.8 mm (1 / 2.8"). Maximum resolution: 3840 x 2160 pixels, Total megapixels: 8 MP, Video compression formats: H.264, H.265, M-JPEG | Vendor Homepage: <https://www.axis.com/products/axis-m4218-v> | Form factor: Dome | Housing material: Aluminium/Polycarbonate (PC) | IK code: IK08 | International Protection (IP) code: IP42 | Mounting type: Ceiling/wall | Product colour: White | Built-in processor: Yes | Certification: CSA, UL/cUL, BIS, UKCA, CE, KC, EAC, VCCI, RCM | Connectivity technology: Wired | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Languages support:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Czech/Dutch/English/Finnish/French/German/Italian/Japanese/Korean/Polish/Portuguese/Russian/Simplified Chinese/Spanish/Swedish/Thai/Traditional Chinese/Turkish/Vietnamese | Number of languages: 19 | Placement supported: Indoor | PTZ control: Yes | PTZ modes: Digital PTZ | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Angle of rotation: 105 | Camera pan control: Yes | Camera shutter speed: 1/71500 - 1/5 | Camera tilt control: Yes | Lens viewing angle, horizontal: 93 - 47 | Lens viewing angle, vertical: 50 - 26 | Minimum illumination: 0.24 | Pan range: -180 - 180 | Tilt angle range: -40 - 65 | Optical sensor size: 1/2.8 | Progressive scan: Yes | Sensor type: CMOS | Maximum aperture number: 2.6 | Minimum aperture number: 1.7 | Zoom capability: Yes | Night vision: No | Frame rate: 15 | Maximum resolution: 3840 x 2160 | Noise reduction: Yes | Noise reduction technology: 2D noise reduction,3D noise reduction | Privacy masking: Yes | Total megapixels: 8 | Video compression formats: H.264/H.265/M-JPEG | Video recording: Yes | Video streaming: Yes | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Networking standards: IEEE 802.1x/IEEE 802.3af/IEEE 802.3at | Quality of Service (QoS) support: Yes | Supported network protocols: IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS, TLS, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP, SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, NTS, RTSP, RTP, SRTP/RTSPS, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCP, ARP, SSH, LLDP, | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash)/MicroSDHC/MicroSDXC | Flash memory: 512 | Internal memory: 2048 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | Active tampering alarm: Yes | Digest authentication: Yes | IP address filtering: Yes | Mirror: Yes | Network access storage (NAS): Yes | Password protection: Yes | Pixel counter: Yes | Video motion detection: Yes | Power consumption (max): 4.8 | Power consumption (Power over Ethernet (PoE)): 3 | Power source type: PoE | Operating relative humidity (H-H): 10 - 85 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -30 - 65 | Diameter: 120 | Height: 71 | Weight: 356 | Manual: Yes | Number of cameras: 1 | Packaging content: Owner authentication key, virtual client license for H.264/H.265 | Product Net Weight: 0.356 | Shipping Box Height: 8.5 | Unit Calculated Volume: 0.001434 | Unit Calculated Weight: 0.47 | Units per Pallet: 0 | Units per Shipping Box: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950