

NET CAMERA 4MP BULLET/HFW5459Z-ZHE-PV-2712-PRO DAHUA

NET CAMERA**4MP****BULLET/HFW5459Z-****ZHE-PV-2712-****PRO DAHUA**

Model: HFW5459Z-ZHE-PV-2712-PRO

Manufacturer: DAHUA

EAN: 6937552410541

Product Code: 405909

R15,208

4MP WizColor Vari-focal Bullet WizMind Network Camera

- > 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image.
- > Outputs max. 4 MP (2688 × 1520) @25/30 fps.
- > Built-in multi-core light, the max. IR distance is 60 m and the max. warm light distance is 60 m.
- > ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments.
- > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- > Features AI Rule Assist, which automatically creates highly accurate IVS rules based on the Xinghan Vision Models.
- > With deep learning algorithm, it supports: AcuPick, video metadata, IVS, face detection, and

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

people counting, etc.

> Alarm: 2 in, 2 out; audio: 1 in, 1 out; RS-485; supports max. 1 TB Micro SD card; built-in dual Mic; 1-ch speaker; support two-way talk.

> 12 VDC/PoE power supply; ePoE; 12 VDC power output, and max. current 165mA, easy for installation.

> IP67 and IK10 protection; Supports window heating

> 2.7 mm-12 mm (98°-48°)

Vendor Homepage: www.dahuasecurity.com/products/All-Products/Network-Cameras/WizMind-5-Series/Pro/4MP/IPC-HFW5459T1-ASE-PV-PRO | Form factor: Bullet | Product colour: White | Connectivity technology: Wired | Adjustment shutter speed: Auto/Manual | Camera shutter speed: 1/3 s-1/100,000 s | Number of effective pixels (H x V): 2688 (H) x 1520 (V) | Optical sensor size: 1/1.8" | Sensor type: CMOS | Focal length range: 2.7 mm-12 mm | LED type: IR/White | Flip & mirror: Yes | Gain control type: Auto/Manual | Image stabilizer: Yes | Noise reduction: Yes | Privacy masking: Yes | Total megapixels: 4 | Built-in microphone: Yes | Built-in speaker(s): Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | Ethernet LAN (RJ-45) ports: 1 | RS-485 ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Power consumption (max): 24.2 | Power consumption (typical): 5.3 | Operating temperature (T-T): -40 °C to +60 °C | Depth: 110.8 | Height: 99.1 | Weight: 1650 | Width: 302.6 | Audio input: 1 | Audio output: 1 | Power source: 12 VDC (±30%); PoE+ (802.3at); ePoE | Product Net Weight: 1.65 | Shipping Box Height: 18 | Unit Calculated Volume: 0.01166 | Unit Calculated Weight: 2.26 | Units per Pallet: 0 | Units per Shipping Box: 1 | Model: IPC-HFW5459Z-ZHE-PV-PRO

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950