

NET CAMERA 4MP EYEBALL/HDW5459T-ZE-IL-2712-B DAHUA

NET CAMERA 4MP EYEBALL/HDW5459T- ZE-IL-2712-B DAHUA



Model: IPC-HDW5459T-ZE-IL-2712-BLACK

Manufacturer: DAHUA

EAN: 6937552412132

Product Code: 405957

R13,365

- 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2688 × 1520) @25/30 fps
- Built-in multi-core light, the max. IR distance is 50 m and the max. warm light distance is 40 m
- ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Powered by the Xinghan Large-Scale AI Models-Vision, the camera outstandingly delivers on its object detection, recognition, and scene adaptation functions
- With deep learning algorithm, it supports: AcuPick, video metadata, IVS, face detection, and people counting, etc

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Supports max. 1 TB Micro SD card; built-in Mic
- 12 VDC/PoE power supply; ePoE
- IP67 protection

Summary: Dahua Technology WizMind IPC-HDW5459T-ZE-IL-2712-Black. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: Black, Form factor: Turret. Minimum illumination: 0.0004 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 115 - 47°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"). Focal length range: 2.7 - 12 mm, Detect distance (wide): 57.5 m, Detect distance (tele): 130.8 m | Vendor Homepage: <https://www.dahuasecurity.com/ceen/products/All-Products/Network-Cameras/WizMind-5-Series/Smart-Dual-Light/4MP/IPC-HDW5459T-ZE-IL> | Form factor: Turret | Housing material: Metal | International Protection (IP) code: IP67 | Mounting type: Ceiling/Wall/Pole | Product colour: Black | Connectivity technology: Wired | Day/night mode: Yes | Dynamic range: 140 | People counting function: Yes | Placement supported: Outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Angle of rotation: 360 | Camera pan control: Yes | Camera shutter speed: 1/3 - 1/100000 | Camera tilt control: Yes | Lens viewing angle, diagonal: 137 - 54 | Lens viewing angle, horizontal: 115 - 47 | Lens viewing angle, vertical: 62 - 27 | Minimum illumination: 0.0004 | Pan range: 0 - 360 | Tilt angle range: 0 - 78 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Optical sensor size: 1/1.8 | Progressive scan: Yes | Sensor type: CMOS | Closest focusing distance: 0.13 | Detect distance (tele): 130.8 | Detect distance (wide): 57.5 | Focal length range: 2.7 - 12 | Identify distance (tele): 13.1 | Identify distance (wide): 5.8 | Maximum aperture number: 1.8 | Observe distance (tele): 52.3 | Observe distance (wide): 23 | Recognize distance (tele): 26.2 | Recognize distance (wide): 11.5 | LED type: IR | Night vision: Yes | Night vision distance: 50 | Number of illumination LEDs: 2 | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR), Variable Bit Rate (VBR) | Frame rate: 30 | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Image stabilizer: Yes | Maximum resolution: 2688 x 1520 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Total megapixels: 4 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Video recording: Yes | Video streaming: Yes | Audio formats supported: G.711 μ -law/G.711 A-law/G.723/G.726/PCM | Built-in microphone: Yes | Signal-to-Noise Ratio (SNR): 56 | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Networking standards: IEEE 802.1x/IEEE 802.3at | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Supported network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, ICMP,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

IGMP, NFS, SAMBA, PPPoE, SNMP, P2P | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | RAM capacity: 2048 | ROM capacity: 4096 | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | Digital watermark: Yes | HTTPS encryption: Yes | Human and vehicle targets classification: Yes | Intelligent Video Surveillance (IVS) system features: Intrusion/People counting/Tripwire | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | DC output voltage: 12 | Power consumption (max): 14.8 | Power consumption (typical): 3.5 | Power source type: DC,PoE | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Diameter: 122 | Height: 108.3 | Weight: 700 | Compliance certificates: CE | Package weight: 960 | Manual: Yes | Number of cameras: 1 | Product Net Weight: 0.7 | Shipping Box Height: 14 | Unit Calculated Volume: 0.003472 | Unit Calculated Weight: 0.98 | Units per Pallet: 0 | Units per Shipping Box: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950