

NET CAMERA 4MP BULLET/HFW5459E1-ZE-IL-2712-B DAHUA

NET CAMERA 4MP BULLET/HFW5459E1- ZE-IL-2712-B DAHUA



Model: IPC-HFW5459E1-ZE-IL-2712-BLACK

Manufacturer: DAHUA

EAN: 6937552412910

Product Code: 405958

R13,365

- 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2688 × 1520) @25/30 fps
- Built-in multi-core light, the max. IR distance is 60 m and the max. warm light distance is 60 m
- ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Powered by the Xinghan Large-Scale AI Models-Vision, the camera outstandingly delivers on its object detection, recognition, and scene adaptation functions
- With deep learning algorithm, it supports: AcuPick, video metadata, IVS, face detection, and people counting, etc

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Alarm: 2 in, 1 out; audio: 1 in, 1 out; supports max. 1 TB Micro SD card; built-in Mic
- 12 VDC/PoE power supply; ePoE
- IP67 and IK10 protection

Summary: Dahua Technology WizMind IPC-HFW5459E1-ZE-IL. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, Form factor: Bullet. Minimum illumination: 0.0007 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 47 - 115°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"). Focal length range: 2.7 - 12 mm, Detect distance (wide): 57.5 m, Detect distance (tele): 130.8 m | Vendor Homepage: <https://www.dahuasecurity.com/ceen/products/All-Products/Network-Cameras/WizMind-5-Series/Smart-Dual-Light/4MP/IPC-HFW5459E1-ZE-IL> | Form factor: Bullet | Housing material: Metal | IK code: IK10 | International Protection (IP) code: IP67 | Mounting type: Ceiling/wall | Product colour: Black | Alarm input/output: Yes | Connectivity technology: Wired | Day/night mode: Yes | People counting function: Yes | Placement supported: Outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Adjustment shutter speed: Auto/Manual | Angle of rotation: 360 | Camera shutter speed: 1/3 - 1/100000 | Camera shutter type: Electronic | Lens viewing angle, diagonal: 54 - 137 | Lens viewing angle, horizontal: 47 - 115 | Lens viewing angle, vertical: 27 - 62 | Minimum illumination: 0.0007 | Pan range: 0 - 360 | Tilt angle range: 0 - 90 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Optical sensor size: 1/1.8 | Progressive scan: Yes | Sensor type: CMOS | Closest focusing distance: 0.13 | Detect distance (tele): 130.8 | Detect distance (wide): 57.5 | Focal length range: 2.7 - 12 | Identify distance (tele): 13.1 | Identify distance (wide): 5.8 | Maximum aperture number: 1.8 | Observe distance (tele): 52.3 | Observe distance (wide): 23 | Recognize distance (tele): 26.2 | Recognize distance (wide): 11.5 | LED type: IR/White | Night vision: Yes | Night vision distance: 60 | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Frame rate: 30 | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Image stabilizer: Yes | Maximum resolution: 2688 x 1520 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Total megapixels: 4 | Video compression formats: H.264/H.264B/H.264H/H.265/H.265+/M-JPEG | Video recording: Yes | Video streaming: Yes | Audio formats supported: G.711 μ -law/G.711 A-law/G.723/G.726/PCM | Audio input channels: 1.0 | Audio output channels: 1.0 | Built-in microphone: Yes | Signal-to-Noise Ratio (SNR): 56 | Bluetooth: No | Ethernet LAN: Yes | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE;

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

SNMP; P2P; Auto Registration | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | RAM capacity: 2000 | ROM capacity: 4000 | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Digital watermark: Yes | HTTPS encryption: Yes | Human and vehicle targets classification: Yes | Intelligent Video Surveillance (IVS) system features: Face detection/People counting/Tripwire | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | Cloud-managed: No | DC output voltage: 12 | Power consumption (max): 20.5 | Power consumption (Power over Ethernet (PoE)): 4.8 | Power consumption (typical): 4.1 | Power source type: DC,PoE | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -40 - 60 | Storage relative humidity (H-H): 0 - 95 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Depth: 279.8 | Height: 94.9 | Weight: 1090 | Width: 96.7 | Compliance certificates: CE/Electromagnetic Compatibility (EMC) | Package type: Box | Package weight: 1390 | Manual: Yes | Number of cameras: 1 | Audio input: RCA | Audio output: RCA | Browser supported: IE: IE 11, Chrome: Chrome 102, Firefox: Firefox 88 | Lens type: Varifocal | Product Net Weight: 1.09 | Shipping Box Height: 33 | Unit Calculated Volume: 0.01138 | Unit Calculated Weight: 1.92 | Units per Pallet: 0 | Units per Shipping Box: 6

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950