

Dahua Technology WizMind IPC-HFW5842T-ASE-0360B-S3 security camera Bullet IP security camera Outdoor 3840 x 2160 pixels Pole clamp



Dahua Technology WizMind IPC- HFW5842T-ASE- 0360B-S3 security camera Bullet IP security camera Outdoor 3840 x 2160 pixels Pole clamp

Model: IPC-HFW5842T-ASE-0360B-S3

Manufacturer: DAHUA

EAN: 6923172588616

Product Code: 405964

R13,069

- 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image
- Outputs max. 8 MP (3840×2160) @25/30fps

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Built-in IR LED, and the max. illumination distance is 80 m
- ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- With deep learning algorithm, it supports: video metadata, smart sound detection, IVS, face detection, smart object detection, and people counting, etc
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 1 TB Micro SD card, built-in MIC
- 12 VDC/PoE power supply; ePoE
- IP67 and IK10 protection
- SMD 3.0

Summary: Dahua Technology WizMind IPC-HFW5842T-ASE-0360B-S3. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Pole clamp, Product colour: White, Form factor: Bullet. Minimum illumination: 0.0004 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 87°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"). Detect distance: 98 m, Observe distance: 39.2 m, Recognize distance: 19.6 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizMind-5-Series/S-Series/8MP/IPC-HFW5842T-ASE=S3> | Form factor: Bullet | Mounting type: Pole clamp | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Dynamic range: 120 | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.0004 | Angle of rotation: 360 | Lens viewing angle, horizontal: 87 | Lens viewing angle, vertical: 49 | Lens viewing angle, diagonal: 99 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter speed: 1/3 - 1/100000 | Number of Privacy masking areas: 8 | Number of sensors: 1 | Optical sensor size: 1/1.8 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 98 | Observe distance: 39.2 | Recognize distance: 19.6 | Fixed focus: Yes | Identify distance: 9.8 | Maximum aperture number: 1.6 | Closest focusing distance: 2.3 | Fixed focal length: 3.6 | Night vision: Yes | Night vision distance: 80 | LED type: IR | Number of illumination LEDs: 4 | Maximum resolution: 3840 x 2160 | Total megapixels: 8 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Video recording: Yes | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Audio formats supported: G.711 μ -law/G.711 A-law/G.723/G.726/PCM | Built-in microphone: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x/IEEE 802.3af | Supported network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP, P2P | Wi-Fi: No | Bluetooth: No | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | ROM capacity: 4096 | RAM capacity: 2048 | Ethernet LAN (RJ-45) ports: 1 | DC-in jack: Yes | Alarm input channels: 1 | Alarm output channels: 1 | Human and vehicle targets classification: Yes | IP address filtering: Yes | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | Power source type: DC,PoE | Power consumption (typical): 4.1 | Power consumption (max): 8.3 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Storage relative humidity (H-H): 10 - 95 | Mobile operating systems supported: Android/iOS | Width: 79 | Height: 75.9 | Length: 244.1 | Weight: 820 | Compliance certificates: CE/Federal Communications Commission (FCC)/UL | Package weight: 1080 | Number of cameras: 1 | Manual: Yes | Unit Calculated Weight: 1.3 | Product Net Weight: 0.82 | Unit Calculated Volume: 0.005038 | Units per Shipping Box: 10 | Units per Pallet: 0 | Shipping Box Height: 26.5 | Name: NET CAMERA 8MP IR BULLET/HFW5842T-ASE-0360B-S3 DAHUA | Model: IPC-HFW5842T-ASE-0360B-S3

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950