



NET CAMERA 12MP/WH UVC- G6-PRO-360-W UBIQUITI



Model: UVC-G6-PRO-360-W

Manufacturer: UBIQUITI

EAN: 810177163237

Product Code: 406000

R11,404

All-weather, vandal-resistant 12MP PoE camera with panoramic 360° coverage, digital pan-tilt-zoom functionality, and smart IR functionality.

Summary: Ubiquiti G6 Pro 360. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Lens viewing angle, horizontal: 180°, Lens viewing angle, vertical: 180°, Lens viewing angle, diagonal: 180°. Optical sensor size: 25.4 / 1.6 mm (1 / 1.6"). Night vision distance: 15 m, LED type: IR | Vendor Homepage: <https://eu.store.ui.com/eu/en/category/cameras-dome-turret/products/uvc-g6-pro-360?variant=uvc-g6-pro-360-w> | Form factor: Dome | Housing material: Aluminium/Polycarbonate (PC) | IK code: IK10 | International Protection (IP) code: IP66 | Mounting type: Ceiling/wall | Product colour: White | Protection features: Vandal proof/Weatherproof | Weatherproof: Yes | Built-in processor: Yes | Connectivity technology: Wired | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Placement supported: Indoor & outdoor | Processor model: ARM Cortex-A53 | Type: IP security camera | Camera pan control: Yes | Camera tilt control: Yes | Lens

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

viewing angle, diagonal: 180 | Lens viewing angle, horizontal: 180 | Lens viewing angle, vertical: 180
| Optical sensor size: 1/1.6 | Number of lenses: 1 | Zoom capability: Yes | LED type: IR | Night vision:
Yes | Night vision distance: 15 | Frame rate: 24 | Image quality adjustment: Brightness/Colour
depth/Contrast/HDR/Sharpness | Maximum resolution: 3504 x 3504 | Noise reduction: Yes | Noise
reduction technology: 2D noise reduction,3D noise reduction | Privacy masking: Yes | Text caption
overlay: Yes | Total megapixels: 12 | Audio system: 2-way | Built-in microphone: Yes | Built-in
speaker(s): Yes | Number of microphones: 2 | Bluetooth: No | Ethernet interface type: Fast Ethernet |
Ethernet LAN: Yes | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory
cards: MicroSD (TransFlash) | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS)
system features: Human detection/Pet detection/Vehicle detection | Reset button: Yes | DC output
voltage: 37,42.5,48,54,57 | Power consumption (max): 7.14 | Power source type: PoE+ | Operating
relative humidity (H-H): 0 - 90 | Operating temperature (T-T): -30 - 50 | Diameter: 147 | Height: 65.5 |
Weight: 610 | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry
Canada (IC)/National Defense Authorization Act (NDAA) | Manual: Yes | Mounting kit: Yes | Number of
cameras: 1 | Screws included: Yes | Night mode: Yes | Units per Pallet: 0 | Units per Shipping Box: 8 |
Unit Calculated Volume: 0.009359 | Unit Calculated Weight: 1.34

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950