



NET CAMERA 12MP/BLK UVC- G6-PRO-360-B UBIQUITI



Model: UVC-G6-PRO-360-B

Manufacturer: UBIQUITI

EAN: 810177163220

Product Code: 406023

R11,534

All-weather, vandal-resistant 12MP PoE camera with panoramic 360° coverage, digital pan-tilt-zoom functionality, and smart IR functionality.

Summary: Ubiquiti G6 Pro 360. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, Form factor: Dome. Lens viewing angle, horizontal: 180°, Lens viewing angle, vertical: 180°, Lens viewing angle, diagonal: 180°. Optical sensor size: 25.4 / 1.6 mm (1 / 1.6"). Night vision distance: 15 m, LED type: IR | Vendor Homepage: <https://eu.store.ui.com/eu/en/category/cameras-dome-turret/products/uvc-g6-pro-360> | Form factor: Dome | Housing material: Aluminium/Polycarbonate (PC) | IK code: IK10 | International Protection (IP) code: IP66 | Mounting type: Ceiling/wall | Product colour: Black | Protection features: Vandal proof/Weatherproof | Weatherproof: Yes | Built-in processor: Yes | Connectivity technology: Wired | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Placement supported: Indoor & outdoor | Processor model: ARM Cortex-A53 | Type: IP security camera | Camera pan control: Yes | Camera tilt control: Yes | Lens viewing angle, diagonal: 180 | Lens viewing angle,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

horizontal: 180 | Lens viewing angle, vertical: 180 | Optical sensor size: 1/1.6 | Number of lenses: 1 | Zoom capability: Yes | LED type: IR | Night vision: Yes | Night vision distance: 15 | Frame rate: 24 | Image quality adjustment: Brightness/Colour depth/Contrast/HDR/Sharpness | Maximum resolution: 3504 x 3504 | Noise reduction: Yes | Noise reduction technology: 2D noise reduction,3D noise reduction | Privacy masking: Yes | Text caption overlay: Yes | Total megapixels: 12 | Audio system: 2-way | Built-in microphone: Yes | Built-in speaker(s): Yes | Number of microphones: 2 | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Ethernet LAN (RJ-45) ports: 1 | Intelligent Video Surveillance (IVS) system features: Human detection/Pet detection/Vehicle detection | Reset button: Yes | DC output voltage: 37,42.5,48,54,57 | Power consumption (max): 7.14 | Power source type: PoE+ | Operating relative humidity (H-H): 0 - 90 | Operating temperature (T-T): -30 - 50 | Diameter: 147 | Height: 65.5 | Weight: 610 | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC)/National Defense Authorization Act (NDAA) | Manual: Yes | Mounting kit: Yes | Number of cameras: 1 | Screws included: Yes | Night mode: Yes | Product Net Weight: 0.61 | Shipping Box Height: 27 | Unit Calculated Volume: 0.0092 | Unit Calculated Weight: 1.34 | Units per Pallet: 0 | Units per Shipping Box: 8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950