

NET CAMERA 4MP BULLET/HFW5459T1ASEPV0280BPROB DAHUA

NET CAMERA**4MP****BULLET/HFW5459T1ASEPV****DAHUA**

Model: IPC-HFW5459T1-ASE-PV-0280B-PRO-BLACK

Manufacturer: DAHUA

EAN: 6937552411081

Product Code: 406031

R11,562

- 4-MP 1/1.8" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2688 × 1520) @25/30 fps
- Built-in multi-core light, the max. IR distance is 80 m and the max. warm light distance is 60 m
- ROI, SVC, SMART H.264+/H.265+, AI H.264/H.265, encoding after filter, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Features AI Rule Assist, which automatically creates highly accurate IVS rules based on the Xinghan Vision Models
- With deep learning algorithm, it supports: AcuPick, video metadata, IVS, face detection, and people counting, etc

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Alarm: 1 in, 1 out; audio: 1 in, 1 out; RS-485; supports max. 1 TB Micro SD card; built-in dual Mic; 1-ch speaker; support two-way talk
- 12 VDC/PoE power supply; ePoE; 12 VDC power output, and max. current 165mA, easy for installation
- IP67 and IK10 protection

Summary: Dahua Technology WizMind IPC-HFW5459T1-ASE-PV-0280B-PRO-Black. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: Black, Form factor: Bullet. Minimum illumination: 0.0001 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 111°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"). Detect distance: 56.6 m, Observe distance: 22.6 m, Recognize distance: 11.3 m | Vendor Homepage: <https://www.dahuasecurity.com/ceen/products/All-Products/Network-Cameras/WizMind-5-Series/Pro/4MP/IPC-HFW5459T1-ASE-PV-PRO> | Form factor: Bullet | Mounting type: Ceiling/Wall/Pole | Product colour: Black | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | People counting function: Yes | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Dynamic range: 140 | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.0001 | Angle of rotation: 360 | Lens viewing angle, horizontal: 111 | Lens viewing angle, vertical: 60 | Lens viewing angle, diagonal: 135 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter speed: 1/3 - 1/100000 | Optical sensor size: 1/1.8 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 56.6 | Observe distance: 22.6 | Recognize distance: 11.3 | Identify distance: 5.7 | Maximum aperture number: 1 | Closest focusing distance: 2 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 80 | LED type: IR | Number of illumination LEDs: 4 | Maximum resolution: 2688 x 1520 | Total megapixels: 4 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Video recording: Yes | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR), Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Built-in speaker(s): Yes | Audio formats supported: G.711 µ-law/G.711 A-law/G.723/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Number of microphones: 2 | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x/IEEE 802.3at | Supported network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, ICMP, IGMP, NFS, SAMBA, PPPoE,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

SNMP, P2P | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 1000 | ROM capacity: 4096 | RAM capacity: 2048 | Ethernet LAN (RJ-45) ports: 1 | RS-485 ports: 1 | DC-in jack: Yes | Alarm input channels: 1 | Alarm output channels: 1 | Digital watermark: Yes | HTTPS encryption: Yes | Human and vehicle targets classification: Yes | Intelligent Video Surveillance (IVS) system features: Intrusion/People counting/Tripwire | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | Power source type: DC,PoE | Power consumption (typical): 4.1 | Power consumption (max): 21.6 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Width: 94.4 | Height: 84.7 | Length: 288.4 | Weight: 1090 | Compliance certificates: CE | Package weight: 1390 | Number of cameras: 1 | Manual: Yes | Unit Calculated Weight: 1.51 | Product Net Weight: 1.09 | Unit Calculated Volume: 0.00714 | Units per Shipping Box: 1 | Unit Width: 34 | Units per Pallet: 0 | Shipping Box Height: 14 | Unit Depth: 15 | Unit Height: 14 | Name: NET CAMERA 4MP BULLET/HFW5459T1ASEPV0280BPROB DAHUA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950