

NET CAMERA 6MP BULLET/HFW3649T1-ASPV0280BPRO-B DAHUA

NET CAMERA 6MP BULLET/HFW3649T1- ASPV0280BPRO- B DAHUA



Model: HFW3649T1-ASPV0280BPRO-B

Manufacturer: DAHUA

EAN: 6939554948251

Product Code: 406080

R10,191

6MP WizColor TiOC PRO Fixed-focal Bullet WizSense Network Camera

- > 1/1.8" CMOS image sensor, low luminance, and high definition image.
- > Outputs max. 6 MP (3288 × 1850)@25/30 fps.
- > H.265 codec, high compression rate, ultra-low bit rate.
- > Built-in multi-core light, the max. IR distance is 50 m and the max. warm light distance is 50 m
- > ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments.
- > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- > Intelligent monitoring: Intrusion, tripwire (the two function support the classification and accurate detection of vehicle and human), stay detection, loitering detection, face detection (full image).

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- > Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.
- > Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 512 G Micro SD card; built-in dual MICs; 1-ch speaker; support two-way talk.
- > 12 VDC/PoE power supply.
- > IP67 protection.
- > Sound and light alarm (red and blue lights).
- > SMD 4.0.
- > Supports AI SSA and one-tap arming and disarming.
- > Focal Length: 2.8 mm
- > Field of View: 109°

Vendor Homepage: www.dahuasecurity.com | Form factor: Bullet | International Protection (IP) code: IP67 | Product colour: Black | Alarm input/output: Yes | Connectivity technology: Wired | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Field of view (FOV) angle: 109 | Minimum illumination: 0.0005 | Number of sensors: 1 | Optical sensor size: 1/1.8 | Sensor type: CMOS | Fixed focal length: 2.8 | B/W night vision distance: 50 | LED type: IR | Night vision: Yes | 3D NR (Noise Reduction): Yes | Back Light Compensation (BLC): Yes | Highlight Compensation (HLC): Yes | Maximum resolution: 3288 × 1850 | Total megapixels: 6 | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 512 | Microphone in: Yes | Alarm input channels: 1 | Alarm output channels: 1 | DC output voltage: 12 | Power consumption (typical): 6.2 | Power source type: DC,PoE | Operating temperature (T-T): -40 °C to +60 °C | Depth: 84.7 | Height: 94.4 | Weight: 1000 | Width: 288.4 | Audio input: 1 | Audio output: 1 | Product Net Weight: 1 | Shipping Box Height: 33 | Unit Calculated Volume: 0.0084645 | Unit Calculated Weight: 1.6 | Units per Shipping Box: 8 | Model: HFW3649T1-ASPV0280B-PRO-B