

NET CAMERA 8MP BULLET/HFW3849T1-ASPV0360B-PROB DAHUA

NET CAMERA 8MP BULLET/HFW3849T1- ASPV0360B- PROB DAHUA



Model: HFW3849T1-ASPV0360B-PRO

Manufacturer: DAHUA

EAN: 6923172592316

Product Code: 406087

R10,137

8MP WizColor TiOC PRO Fixed-focal Bullet WizSense Network Camera

- 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image
- Outputs max. 8 MP (3840 × 2160)@25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in multi-core light, the max. IR distance is 50 m and the max. warm light distance is 50 m
 - ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Intelligent monitoring: Intrusion, tripwire (the two function support the classification and accurate detection of vehicle and human), stay detection, loitering detection, face detection (full image)
- Abnormality detection: Motion detection, privacy masking, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 512 G Micro SD card; built-in dual MICs; 1-ch speaker; support two-way talk
- 12 VDC/PoE power supply
- IP67 protection
- Sound and light alarm (red and blue lights)
- SMD 4.0
- Supports AI SSA and one-tap arming and disarming
- SMD area can be set in warm light areas that support triggering alarms

Summary: Dahua Technology WizSense IPC-HFW3849T1-AS-PV-PRO. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Bullet. Minimum illumination: 0.007 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 360°. Sensor type: CMOS, Optical sensor size: 25.4 / 1.8 mm (1 / 1.8"). Detect distance: 91 m, Observe distance: 36.4 m, Recognize distance: 18.2 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/3-Series/TiOC-PRO-WizColor/IPC-HFW3849T1-AS-PV-PRO> | Form factor: Bullet | Mounting type: Ceiling/wall | Product colour: White | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Alarm input/output: Yes | Dynamic range: 120 | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive; 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B | Minimum illumination: 0.007 | Angle of rotation: 360 | Lens viewing angle, horizontal: 360 | Lens viewing angle, vertical: 90 | Lens viewing angle, diagonal: 360 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of Privacy masking areas: 4 | Number of sensors: 1 | Optical sensor size: 1/1.8 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 91 | Observe distance: 36.4 | Recognize distance: 18.2 | Identify distance: 9.1 | Closest focusing distance: 4.4 | Fixed focal length: 3.6 | Night vision: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Night vision distance: 30 | LED type: White | Number of illumination LEDs: 2 | Maximum resolution: 3840 x 2160 | Total megapixels: 8 | Video formats supported: H.264/H.264+/H.264B/H.265/H.265+ | Video compression formats: H.264/H.264+/H.264B/H.265/H.265+ | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2048 x 1536 (QXGA)/2304 x 1296/2592 x 1944/2668 x 1512/2688 x 1512/3072 x 1728/3072 x 2048/352 x 240/352 x 288/3840 x 2160/640 x 480 (VGA)/704 x 480/704 x 576 | Frame rate: 20 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: 3 kbps-20480 kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Smart IR: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: G.711 A-law/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; SNMP | Wi-Fi: No | Bluetooth: No | Number of users: 20 | Live view: Yes | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Internal memory: 512 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Video motion detection: Yes | Power source type: DC,PoE | Power consumption (typical): 4.5 | Power consumption (max): 76 | Power consumption (Power over Ethernet (PoE)): 9.1 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Width: 94.4 | Height: 84.7 | Length: 288.4 | Number of cameras: 1 | Unit Calculated Weight: 1.595 | Product Net Weight: 1 | Unit Calculated Volume: 0.008208 | Units per Shipping Box: 8 | Unit Width: 34 | Units per Pallet: 0 | Shipping Box Height: 32 | Unit Depth: 15 | Unit Height: 13.5 | Name: NET CAMERA 8MP BULLET/HFW3849T1-ASPV0360B-PROB DAHUA | Model: HFW3849T1-ASPV0360B-PRO-B

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950