



NET CAMERA M3085-V 2MP/02373-001 AXIS



Model: 02373-001

Manufacturer: AXIS

EAN: 7331021076631

Product Code: 406115

R9,404

This cost-efficient mini dome features Wide Dynamic Range (WDR) to ensure clarity even when there's both dark and light areas in the scene. With Lightfinder, it delivers sharp color images even in low light. A deep learning processing unit enables intelligent analytics based on deep learning on the edge. And AXIS Object Analytics offers detection and classification of different types of objects – all tailored to your specific needs. Furthermore, this compact, easy-to-install, vandal-resistant camera comes factory focused so there's no manual focusing required.

- Built-in cybersecurity features; Compact, discreet design; Great image quality in 2 MP; Support for analytics with deep learning; WDR and Lightfinder

Summary: Axis 02373-001. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Lens viewing angle, horizontal: 102°, Lens viewing angle, vertical: 55°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Fixed focal length: 3.1 mm | Vendor Homepage: _____

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

<https://www.axis.com/products/axis-m3085-v> | Form factor: Dome | IK code: IK08 | International Protection (IP) code: IP42 | Mounting type: Ceiling/wall | Product colour: White | Connectivity technology: Wired | Day/night mode: Yes | Placement supported: Indoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Lens viewing angle, horizontal: 102 | Lens viewing angle, vertical: 55 | Optical sensor size: 1/2.9 | Sensor type: CMOS | Fixed focal length: 3.1 | Night vision: Yes | Maximum resolution: 1920 x 1080 | Total megapixels: 2 | Video compression formats: H.264H/H.264M/H.265 | Video streaming: Yes | Audio system full duplex: Yes | Bluetooth: No | Ethernet LAN: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Compatible memory cards: MicroSD (TransFlash)/MicroSDHC/MicroSDXC | Ethernet LAN (RJ-45) ports: 1 | Motion sensor: Yes | Power consumption (max): 4.2 | Power consumption (typical): 3.6 | Power source type: PoE | Operating relative humidity (H-H): 10 - 85 | Operating temperature (T-T): 0 - 45 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 65 | Diameter: 101 | Height: 56 | Weight: 150 | Number of cameras: 1 | Doesn't contain: BFR/PVC | Product Net Weight: 0.25 | Shipping Box Height: 9 | Unit Calculated Volume: 0.001188 | Unit Calculated Weight: 0.28 | Units per Shipping Box: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950