

NET CAMERA M3085-V 2MP/02373-001 AXIS

Model: 02373-001

Manufacturer: AXIS

EAN: 7331021076631

Product Code: 406115

R9,404

This cost-efficient mini dome features Wide Dynamic Range (WDR) to ensure clarity even when there’s both dark and light areas in the scene. With Lightfinder, it delivers sharp color images even in low light. A deep learning processing unit enables intelligent analytics based on deep learning on the edge. And AXIS Object Analytics offers detection and classification of different types of objects – all tailored to your specific needs. Furthermore, this compact, easy-to-install, vandal-resistant camera comes factory focused so there’s no manual focusing required.

- Built-in cybersecurity features; Compact, discreet design; Great image quality in 2 MP; Support for analytics with deep learning; WDR and Lightfinder

Summary: Axis 02373-001. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: White, Form factor: Dome. Lens viewing angle, horizontal: 102°, Lens viewing angle, vertical: 55°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Fixed focal length: 3.1 mm | Vendor Homepage:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

https://www.axis.com/products/axis-m3085-v | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: White | International Protection (IP) code: IP42 | IK code: IK08 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Lens viewing angle, horizontal: 102 | Lens viewing angle, vertical: 55 | Optical sensor size: 1/2.9 | Sensor type: CMOS | Fixed focal length: 3.1 | Night vision: Yes | Maximum resolution: 1920 x 1080 | Total megapixels: 2 | Video compression formats: H.264H/H.264M/H.265 | Video streaming: Yes | Audio system full duplex: Yes | Ethernet LAN: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Bluetooth: No | Compatible memory cards: MicroSD (TransFlash)/MicroSDHC/MicroSDXC | Ethernet LAN (RJ-45) ports: 1 | Motion sensor: Yes | Power source type: PoE | Power consumption (typical): 3.6 | Power consumption (max): 4.2 | Operating temperature (T-T): 0 - 45 | Storage temperature (T-T): -40 - 65 | Operating relative humidity (H-H): 10 - 85 | Storage relative humidity (H-H): 5 - 95 | Height: 56 | Diameter: 101 | Weight: 150 | Number of cameras: 1 | Doesn't contain: BFR/PVC | Unit Calculated Weight: 0.28 | Product Net Weight: 0.25 | Unit Calculated Volume: 0.001188 | Units per Shipping Box: 1 | Unit Width: 11 | Shipping Box Height: 9 | Unit Depth: 12 | Unit Height: 9 | Name: NET CAMERA M3085-V 2MP/02373-001 AXIS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950