



NET CAMERA 8MP/UVC-G5- PRO UBIQUITI



Model: UVC-G5-PRO

Manufacturer: UBIQUITI

EAN: 810084690246

Product Code: 406200

R7,750

Indoor/outdoor 4K PoE Camera with exceptional image performance and 3x optical zoom lens.

- 4K (8MP) video resolution
- 3x optical zoom
- 25 m (82 ft) IR night vision
- AI event detections
- Built-in IR LEDs and an automatic IR cut filter
- Record audio with an integrated microphone
- Connect and power using PoE
- Optional Enhancer for integrated floodlight and extended IR
- Weatherproof (outdoor exposed)

Summary: Ubiquiti G5 Professional. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Bullet. Lens viewing angle, horizontal: 35, 109.9°, Lens viewing angle, vertical: 19.8,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

60°, Lens viewing angle, diagonal: 40, 127.7°. Optical sensor size: 25.4 / 2 mm (1 / 2"). Optical zoom: 3x, Focal length range: 4.1 - 12.3 mm | Vendor Homepage: <https://store.ui.com/us/en/products/uvc-g5-pro?variant=UVC-G5-Pro> | Form factor: Bullet | Housing material: Aluminium/Polycarbonate (PC) | IK code: IK04 | International Protection (IP) code: IP65 | Mounting type: Ceiling/Wall/Pole | Product colour: White | Weatherproof: Yes | Built-in processor: Yes | Certification: FCC, IC, CE | Connectivity technology: Wired | Infrared (IR) cut-off filter: Yes | Placement supported: Indoor & outdoor | Type: IP security camera | Lens viewing angle, diagonal: 40, 127.7 | Lens viewing angle, horizontal: 35, 109.9 | Lens viewing angle, vertical: 19.8, 60 | Optical sensor size: 1/2 | Focal length range: 4.1 - 12.3 | Maximum aperture number: 3.3 | Minimum aperture number: 1.53 | Optical zoom: 3 | Zoom capability: Yes | LED type: IR | Night vision: Yes | Night vision distance: 25 | Frame rate: 30 | Image quality adjustment: Brightness/Contrast/Sharpness | Maximum resolution: 3840 x 2160 | Noise reduction: Yes | Noise reduction technology: 2D noise reduction, 3D noise reduction | Total megapixels: 8 | Video compression formats: H.264 | Built-in microphone: Yes | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Wi-Fi: No | Built-in HDD: No | Ethernet LAN (RJ-45) ports: 1 | Reset button: Yes | DC output voltage: 37,48,54,57 | Power consumption (max): 10 | Power source type: PoE | Operating relative humidity (H-H): 0 - 90 | Operating temperature (T-T): -20 - 50 | Diameter: 86 | Length: 154.3 | Weight: 650 | Manual: Yes | Mounting kit: Yes | Number of cameras: 1 | Units per Shipping Box: 6 | Unit Calculated Volume: 0.006593 | Unit Calculated Weight: 1.13

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950