

Dahua Technology WizSense IPC-HDBW2441R-ZAS-27135 Dome IP security camera Outdoor 2688 x 1520 pixels Ceiling



Dahua Technology WizSense IPC- HDBW2441R- ZAS-27135 Dome IP security camera Outdoor 2688 x 1520 pixels Ceiling

Model: IPC-HDBW2441R-ZAS-27135

Manufacturer: DAHUA

EAN: 6923172545671

Product Code: 406241

R7,372

- 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2688 × 1520)@20 fps and supports 2560 × 1440 (2560 × 1440)@25/30 fps

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED, and the max. illumination distance is 40 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Alarm: 1 in, 1 out (Only - ZAS supports); audio: 1 in, 1 out (Only - ZAS supports); supports max. 256 G Micro SD card; built in MIC
- 12 VDC/PoE power supply, easy for installation
- IP67 and IK10 protection
- SMD Plus

Summary: Dahua Technology WizSense IPC-HDBW2441R-ZAS-27135. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling, Product colour: White, Form factor: Dome. Angle of rotation: 355°, Lens viewing angle, horizontal: 104 - 29°, Lens viewing angle, vertical: 54 - 16°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Focal length range: 2.7 - 13.5 mm, Detect distance (wide): 64 m, Detect distance (tele): 210 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/2-Series/4MP/IPC-HDBW2441R-ZAS> | Form factor: Dome | Mounting type: Ceiling | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Dynamic range: 120 | Minimum illumination: 0 | Angle of rotation: 355 | Lens viewing angle, horizontal: 104 - 29 | Lens viewing angle, vertical: 54 - 16 | Lens viewing angle, diagonal: 125 - 34 | Tilt angle range: 0 - 75 | Pan range: 0 - 355 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of Privacy masking areas: 4 | Optical sensor size: 1/2.9 | Progressive scan: Yes | Sensor type: CMOS | Focal length range: 2.7 - 13.5 | Minimum aperture number: 1.5 | Closest focusing distance: 0.8 | Detect distance (tele): 210 | Detect distance (wide): 64 | Identify distance (tele): 21 | Identify distance (wide): 6.4 | Observe distance (tele): 84 | Observe distance (wide): 25.6 | Recognize

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

distance (tele): 42 | Recognize distance (wide): 12.8 | Night vision: Yes | Night vision distance: 40 | LED type: IR | Number of illumination LEDs: 2 | Maximum resolution: 2688 x 1520 | Total megapixels: 4 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2560 x 1440/2688 x 1520/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: 12 kbps-6144 kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Built-in speaker(s): Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Audio formats supported: G.711 μ -law/G.711 A-law/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Built-in microphone: Yes | Ethernet LAN: Yes | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP | Wi-Fi: No | Bluetooth: No | Number of users: 6 | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Flash memory: 128 | Internal memory: 128 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Mirror: Yes | Video motion detection: Yes | Web browser: No | Management software: Smart PSS; DSS; DMSS | Power source type: DC,PoE | Power consumption (typical): 2.3 | Power consumption (max): 6.5 | Power consumption (Power over Ethernet (PoE)): 3.2 | DC output voltage: 12 | Operating temperature (T-T): -30 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Height: 93.4 | Diameter: 122 | Weight: 520 | Package weight: 680 | Number of cameras: 1 | Unit Calculated Weight: 0.68 | Product Net Weight: 0.52 | Unit Calculated Volume: 0.003584 | Units per Shipping Box: 1 | Unit Width: 16 | Shipping Box Height: 14 | Unit Depth: 16 | Unit Height: 14 | Name: NET CAMERA 4MP IR DOME/IPC-HDBW2441R-ZAS-27135 DAHUA | Model: IPC-HDBW2441R-ZAS-27135

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950