

NET CAMERA 6MP DOME/HDBW3649E-AS-IL-0280B DAHUA

Model: DH-IPC-HDBW3649E-AS-IL-0280B

Manufacturer: DAHUA

EAN: 6939554919961

Product Code: 406244

R7,345

> 6-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.
> Outputs max. 6 MP (3288 1850)@25/30 fps.
> H.265 codec, high compression rate, ultra-low bit rate.
> Built-in IR LED and warm light , the max. IR illumination distance is 30 m and the max. warm light distance is 30 m.
> ROI, SMART H.264+/H.265+, AI H.264/H.265, flexible coding, applicable to various bandwidth and storage environments.
> Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
> Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human), stay detection, loitering detection; face detection (full image).

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

> Abnormality detection: Motion detection, video tampering, scene changing, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.

> Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 512 G Micro SD card; built-in Mic.

> 12 VDC/PoE power supply.

> IP67 and IK10 protection.

> SMD 4.0.

> Supports AI SSA.

> SMD area can be set in warm light areas that support triggering alarms.

> Focal Length 2.8 mm, Field of View 110°

Vendor Homepage: www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/3-Series/Smart-Dual-Light/IPC-HDBW3649E-AS-IL | Form factor: Dome | Connectivity technology: Wired | Adjustment shutter speed: Auto/Manual | Camera shutter speed: 1/3 s1/100,000 s | Effective sensor resolution: 6 | Optical sensor size: 1/2.7" | Sensor type: CMOS | Fixed focal length: 2.8 | B/W night vision distance: 30 | Night vision: Yes | Audio input channels: 1.0 | Audio output channels: 1.0 | Built-in microphone: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 512 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | DC output voltage: 12 | Power consumption (max): 7.5 | Power over Ethernet (PoE): Yes | Operating temperature (T-T): -40 C to +60 C | Lens mount interface: M12 | Product Net Weight: 0.528 | Shipping Box Height: 28 | Unit Calculated Volume: 0.00286 | Unit Calculated Weight: 0.79 | Units per Pallet: 0 | Units per Shipping Box: 24

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950