

NET CAMERA 8MP IR EYEBALL/IPC-HDW2849TM-S-IL-0280B DAHUA



NET CAMERA 8MP IR EYEBALL/IPC- HDW2849TM-S- IL-0280B DAHUA

Model: IPC-HDW2849TM-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172581549

Product Code: 406515

R5,011

8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera

- 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image
- Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688 × 1520 (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Supports max. 256 G Micro SD card; built in MIC
- 12 VDC/PoE power supply, easy for installation
- IP67 protection
- SMD Plus

Summary: Dahua Technology WizSense DH-IPC-HDW2849TMP-S-IL-0280B. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Dome. Angle of rotation: 360°, Tilt angle range: 0 - 78°, Pan range: 0 - 360°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Night vision distance: 30 m, LED type: IR | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/2-Series/Smart-Dual-Light/IPC-HDW2849TM-S-IL> | Form factor: Dome | International Protection (IP) code: IP67 | Mounting type: Ceiling/Wall/Pole | Product colour: White | Protection features: Dust resistant | Built-in light: Yes | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; FCC: 47 CFR FCC Part 15, Subpart B; UL/CUL: UL62368-1 & CAN/CSA C22.2 No. 62368-1-14 | Connectivity technology: Wired | Day/night mode: Yes | Infrared (IR) cut-off filter: Yes | Placement supported: Outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Angle of rotation: 360 | Camera shutter speed: 1/3 - 1/100000 | Camera shutter type: Electronic | Pan range: 0 - 360 | Tilt angle range: 0 - 78 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Minimum aperture number: 1.6 | Number of lenses: 2.8 | LED type: IR | Night vision: Yes | Night vision distance: 30 | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Flip & mirror: Yes | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Maximum resolution: 3840 x 2160 | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2048 x 1536 (QXGA)/2304 x 1296/2688 x 1520/2880 x 1620/3072 x 1728/3072 x 2048/352 x 240/352 x 288/3840 x 2160/640 x 480 (VGA)/704 x 480/704 x 576 | Total megapixels: 8 | Video compression formats: H.264/H.264+/H.264B/H.264H/H.265/H.265+/M-JPEG | Video streaming: Yes | Audio formats

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

supported: G.711 μ -law/G.711 A-law/G.726/PCM | Signal-to-Noise Ratio (SNR): 56 | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Number of users: 20 | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour | Internal memory: 256 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Active tampering alarm: Yes | Intelligent Video Surveillance (IVS) system features: Intrusion/Tripwire | Video motion detection: Yes | Management software: Smart PSS; DSS; DMSS | Web browser: Yes | DC output voltage: 12 | Power consumption (typical): 2.6 | Power source type: DC,PoC | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -40 - 55 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Diameter: 121.9 | Weight: 480 | Width: 99.1 | Package weight: 620 | Number of cameras: 1 | Product Net Weight: 0.48 | Shipping Box Height: 26 | Unit Calculated Volume: 0.002769 | Unit Calculated Weight: 0.71 | Units per Pallet: 0 | Units per Shipping Box: 20 | Model: IPC-HDW2849TM-S-IL-0280B

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950