

NET CAMERA 8MP BULLET/IPC-HFW2849S-S-IL-0280B DAHUA



NET CAMERA 8MP BULLET/IPC- HFW2849S-S-IL- 0280B DAHUA

Model: IPC-HFW2849S-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172581570

Product Code: 406522

R4,956

8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera

- 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image
- Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in warm light and IR LED, the max. illumination distance is 30 m and the max. warm light distance is 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Supports max. 256 G Micro SD card; built in MIC
- 12 VDC/PoE power supply, easy for installation
- IP67 protection
- SMD Plus

Summary: Dahua Technology WizSense IPC-HFW2849S-S-IL. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product colour: Black, White, Form factor: Bullet. Angle of rotation: 360°, Lens viewing angle, horizontal: 111°, Lens viewing angle, vertical: 58°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 84.8 m, Observe distance: 33.9 m, Recognize distance: 17 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/2-Series/Smart-Dual-Light/IPC-HFW2849S-S-IL> | Form factor: Bullet | Housing material: Metal | International Protection (IP) code: IP67 | Mounting type: Ceiling/wall | Product colour: Black/White | Protection features: Waterproof | Alarm input/output: Yes | Built-in light: Yes | Connectivity technology: Wired | Day/night mode: Yes | Dynamic range: 120 | Placement supported: Indoor & outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Adjustment shutter speed: Auto/Manual | Angle of rotation: 360 | Camera shutter speed: 1/3 - 1/100000 | Camera shutter type: Electronic | Lens viewing angle, diagonal: 132 | Lens viewing angle, horizontal: 111 | Lens viewing angle, vertical: 58 | Minimum illumination: 0 | Number of Privacy masking areas: 4 | Pan range: 0 - 360 | Tilt angle range: 0 - 90 | White balance: Auto/Manual/Natural/Outdoor/Street lamp | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Closest focusing distance: 1.5 | Detect distance: 84.8 | Fixed focal length: 2.8 | Identify distance: 8.5 | Maximum aperture number: 1.6 | Number of lenses: 1 | Observe distance: 33.9 | Recognize distance: 17 | B/W night vision distance: 30 | LED type: IR/White | Night vision: Yes | Night vision distance: 30 | Number of illumination LEDs: 2 | Back Light Compensation (BLC): Yes | Bit rate: 12 Kbps - 8192 Kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Maximum resolution: 3840 x 2160 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Privacy masking: Yes | Region of Interest (ROI) encoding: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Smart IR: Yes | Supported graphics resolutions: 1280 x 720 (HD 720)/1920 x 1080 (HD 1080)/2048 x 1536 (QXGA)/2304 x 1296/2688 x 1512/2880 x 1620/3072 x 1728/3072 x 2048/352 x 240/352 x 288/3840 x 2160/640 x 480 (VGA)/704 x 480/704 x 576 | Total megapixels: 8 | Video compression formats: H.264/H.264+/H.264B/H.265/H.265+ | Video streaming: Yes | Built-in microphone: Yes | Signal-to-Noise Ratio (SNR): 56 | Voice codecs: G.711a/G.711Mu/G.726/PCM | Bluetooth: No | Client interoperability: ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Networking standards: IEEE 802.3af | Number of users: 20 | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; Bonjour | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | RAM capacity: 256 | ROM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Alarm input channels: 1 | Alarm output channels: 1 | Intelligent Video Surveillance (IVS) system features: Intrusion/Tripwire | Mirror: Yes | Network access storage (NAS): Yes | Privacy protection: Yes | Video motion detection: Yes | Management software: Smart PSS, DSS, DMSS | Web browser: Yes | DC output voltage: 12 | Power consumption (max): 5 | Power consumption (Power over Ethernet (PoE)): 5.9 | Power consumption (typical): 2.7 | Power source type: DC,PoE | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -40 - 55 | Storage relative humidity (H-H): 0 - 95 | Storage temperature (T-T): -40 - 55 | Mobile operating systems supported: Android/iOS | Height: 70 | Length: 166.2 | Weight: 470 | Width: 70 | Package weight: 590 | Manual: Yes | Number of cameras: 2 | Browser supported: IE: IE8, IE9, IE11 Chrome Firefox, Safari | Lens mount interface: M12 | Number of video streams: 2 | Model: IPC-HFW2849S-S-IL-0280B | Units per Pallet: 0 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.002649 | Unit Calculated Weight: 0.655

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950