

Dahua Technology WizSense IPC-HFW2649S-S-IL-0280B security camera Bullet IP security camera Indoor 3288 x 1850 pixels Pole clamp door 3



Dahua Technology WizSense IPC- HFW2649S-S-IL- 0280B security camera Bullet IP security camera Indoor 3288 x 1850 pixels Pole clamp

Model: IPC-HFW2649S-S-IL-0280B

Manufacturer: DAHUA

EAN: 6939554905261

Product Code: 406539

R4,825

- 1/2.7" CMOS image sensor, low luminance, and high definition image
- Outputs max. 6 MP (3288×1850) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Built-in warm light and IR LED, the max. IR distance is 30 m and the max. warm light distance is 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Supports max. 256 G Micro SD card; built in Mic
- 12 VDC/PoE power supply, easy for installation

Summary: Dahua Technology WizSense IPC-HFW2649S-S-IL-0280B. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Pole clamp, Product colour: White, Form factor: Bullet. Minimum illumination: 0.0007 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 112°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 61.2 m, Observe distance: 24.5 m, Recognize distance: 12.2 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/2-Series/Smart-Dual-Light/IPC-HFW2649S-S-IL> | Form factor: Bullet | Housing material: Metal | International Protection (IP) code: IP67 | Mounting type: Pole clamp | Product colour: White | Connectivity technology: Wired | Day/night mode: Yes | Dynamic range: 120 | Placement supported: Indoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Angle of rotation: 360 | Camera pan control: Yes | Camera shutter speed: 1/3 - 1/100000 | Camera tilt control: Yes | Lens viewing angle, diagonal: 132 | Lens viewing angle, horizontal: 112 | Lens viewing angle, vertical: 61 | Minimum illumination: 0.0007 | Number of Privacy masking areas: 4 | Pan range: 0 - 360 | Tilt angle range: 0 - 90 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Closest focusing distance: 1 | Detect distance: 61.2 | Fixed focal length: 2.8 | Fixed focus: Yes | Identify distance: 6.1 | Maximum aperture number: 1.6 | Observe distance: 24.5 | Recognize distance: 12.2 | Colour night vision distance: 30 | LED type: IR | Night vision: Yes | Night vision distance: 30 | Number of illumination LEDs: 2 | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Frame rate: 30 | Gain control type: Auto/Manual | Highlight Compensation (HLC): Yes | Maximum resolution: 3288 x 1850 | Noise reduction: Yes | Noise reduction

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

technology: 3D noise reduction | Region of Interest (ROI) encoding: Yes | Total megapixels: 6 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Video recording: Yes | Video streaming: Yes | Audio formats supported: G.711 μ -law/G.711 A-law/G.726/PCM | Built-in microphone: Yes | Bluetooth: No | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Networking standards: IEEE 802.1x | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Supported network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, ICMP, IGMP, NFS, PPPoE, P2P | Wi-Fi: No | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | RAM capacity: 256 | ROM capacity: 128 | DC-in jack: Yes | Ethernet LAN (RJ-45) ports: 1 | Human and vehicle targets classification: Yes | IP address filtering: Yes | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | DC output voltage: 12 | Power consumption (max): 4.4 | Power consumption (typical): 2.5 | Power source type: DC,PoE | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Height: 70 | Length: 169.8 | Weight: 470 | Width: 70 | Compliance certificates: CE | Package weight: 590 | Manual: Yes | Number of cameras: 1 | Product Net Weight: 0.47 | Shipping Box Height: 23 | Unit Calculated Volume: 0.00272 | Unit Calculated Weight: 0.65 | Units per Pallet: 0 | Units per Shipping Box: 20

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950