

Dahua Technology WizSense IPC-HDW2649TM-S-IL-0280B security camera Turret IP secu



Indoor

Dahua Technology WizSense IPC- HDW2649TM-S- IL-0280B security camera Turret IP security camera Indoor 3288 x 1850 pixels Ceiling/Wall/Pole

Model: IPC-HDW2649TM-S-IL-0280B

Manufacturer: DAHUA

EAN: 6939554905285

Product Code: 406594

R4,488

- 1/2.7" CMOS image sensor, low luminance, and high definition image
- Outputs max. 6 MP (3288×1850) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- H.265 codec, high compression rate, ultra-low bit rate
- Built-in warm light and IR LED, the max. IR distance is 30 m and the max. warm light distance is 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Supports max. 256 G Micro SD card; built in Mic
- 12 VDC/PoE power supply, easy for installation

Summary: Dahua Technology WizSense IPC-HDW2649TM-S-IL-0280B. Type: IP security camera, Placement supported: Indoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.0007 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 112°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Detect distance: 61.2 m, Observe distance: 24.5 m, Recognize distance: 12.2 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/WizSense-Series/2-Series/Smart-Dual-Light/IPC-HDW2649TM-S-IL> | Form factor: Turret | Mounting type: Ceiling/Wall/Pole | Product colour: White | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Indoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Dynamic range: 120 | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.0007 | Angle of rotation: 360 | Lens viewing angle, horizontal: 112 | Lens viewing angle, vertical: 61 | Lens viewing angle, diagonal: 132 | Tilt angle range: 0 - 78 | Pan range: 0 - 360 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter speed: 1/3 - 1/100000 | Number of Privacy masking areas: 4 | Number of sensors: 1 | Optical sensor size: 1/2.7 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 61.2 | Observe distance: 24.5 | Recognize distance: 12.2 | Fixed focus: Yes | Identify distance: 6.1 | Maximum aperture number: 1.6 | Closest focusing distance: 1 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 30 | Colour night vision distance: 30 | LED type: IR | Number of illumination LEDs: 2 | Maximum resolution: 3288 x 1850 | Total megapixels: 6 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Video recording: Yes | Frame rate: 30 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Audio formats supported: G.711 μ -law/G.711 A-law/G.726/PCM | Built-in microphone: Yes | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.1x | Supported network protocols: IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, ICMP, IGMP, NFS, PPPoE, P2P | Wi-Fi: No | Bluetooth: No | Quality of Service (QoS) support: Yes | Streaming method: Multicast | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | ROM capacity: 128 | RAM capacity: 256 | Ethernet LAN (RJ-45) ports: 1 | DC-in jack: Yes | Human and vehicle targets classification: Yes | IP address filtering: Yes | Mirror: Yes | Network access storage (NAS): Yes | Video motion detection: Yes | Power source type: DC,PoE | Power consumption (typical): 2.5 | Power consumption (max): 4.6 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Mobile operating systems supported: Android/iOS | Height: 99.1 | Diameter: 121.9 | Weight: 530 | Compliance certificates: CE | Package weight: 670 | Number of cameras: 1 | Manual: Yes | Unit Calculated Weight: 0.725 | Product Net Weight: 0.53 | Unit Calculated Volume: 0.002769 | Units per Shipping Box: 20 | Unit Width: 14 | Units per Pallet: 0 | Shipping Box Height: 26 | Unit Depth: 14 | Unit Height: 11 | Name: NET CAMERA 6MP EYEBALL/IPC-HDW2649TM-S-IL-0280B DAHUA | Model: IPC-HDW2649TM-S-IL-0280B

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950