



DVR 4CH HDCVI PENTABRID AI/XVR5104HS- I3/T DAHUA



Model: XVR5104HS-I3/T

Manufacturer: DAHUA

EAN: 6937552414907

Product Code: 406621

R4,408

- 4-ch Analog Video Input, Max. 5M-N@25fps/1080p@25fps Encoding Capability
- Max. 6-ch IP Video Input (Up to 6MP)
- 4-ch Two-way Talk
- AI Functions: 2-ch AcuPick, 2-ch FR, 4-ch Perimeter Protection, 4-ch SMD, 4-ch AI Coding
- 1 Bay. Up to 16TB for Each HDD Storage Capacity

Summary: Dahua Technology XVR5104HS-I3/T. Product colour: Black, Maximum video resolution: 1920 x 1080 pixels, Video compression formats: H.264, H.264+, H.265, H.265+. Video input channels: 4 channels, Audio input: 1 RCA, Audio output: 1 RCA. Ethernet interface type: Fast Ethernet, Supported network protocols: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P. HDD interface: SATA, Maximum HDD capacity: 16 TB. Power supply type: DC, DC voltage: 12 V, Power consumption (typical): 4 W | Vendor Homepage: <https://www.dahuasecurity.com/products/hdcvi-products/hdcvi-recorders/5mp-value-1080p->

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

series/xvr5104hs-i3/t | Audio input: 1 RCA | Audio output: 1 RCA | BNC input ports: 4 | BNC output ports: 1 | HDMI ports quantity: 1 | RS-485 ports: 1 | USB 2.0 ports quantity: 2 | VGA (D-Sub) output ports: 1 | Video input channels: 4 | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Ethernet LAN (RJ-45) ports: 1 | Supported network protocols: HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; P2P | HDD interface: SATA | Maximum HDD capacity: 16000 | Number of HDDs supported: 1 | Analog signal format system: NTSC/PAL | Audio formats supported: G.711 μ -law/G.711 A-law/PCM | Audio system: 2-way | Backup function: Yes | Certification: FCC: Part 15 Subpart B CE: CE-LVD: EN 60950-1/IEC 60950-1 CE-EMC: EN 61000-3-2; EN 61000-3-3; EN 55032; EN50130; EN 55024 | Channels quantity: 4 | Dual stream support: Yes | Maximum frame rate: 60 | Maximum video resolution: 1920 x 1080 | Operating system installed: Embedded LINUX | Playback resolutions supported: 1920 x 1080, 1280 x 1024, 1280 x 720 | Product colour: Black | PTZ control: Yes | Rack capacity: 1U | Video capturing speed: 30 | Video compression formats: H.264/H.264+/H.265/H.265+ | Video loss detection: Yes | Video motion detection: Yes | Video streaming: Yes | DC voltage: 12 | Power consumption (typical): 4 | Power supply type: DC | Depth: 237.9 | Height: 47.6 | Weight: 840 | Width: 260 | Package depth: 89 | Package height: 287 | Package weight: 1410 | Package width: 344 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 55 | Product Net Weight: 0.84 | Shipping Box Height: 32 | Unit Calculated Volume: 0.01063 | Unit Calculated Weight: 1.56 | Units per Pallet: 0 | Units per Shipping Box: 10 | Model: XVR5104HS-I3/T

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950