



DVR 16CH HDCVI PENTABRID/XVR1B16- I/T DAHUA



Model: XVR1B16-I/T

Manufacturer: DAHUA

EAN: 6937552407985

Product Code: 406660

R4,266

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

The Cooper-I/T Series offers simple and highly cost-effective HDCVI solutions. It provides 24/7 reliable monitoring with high-quality image performance, saving you on labor costs. It also includes a two-way talk function that is supported by all the channels and operates over coaxial cable, along with SMD Plus, offering you excellent value.

- 16-ch Analog Video Input, Max. 1080N/720p@15fps Encoding Capability
- Max. 18-ch IP Video Input (Up to 6MP)
- 16-ch Two-way Talk

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- AI Functions: 16-ch SMD, 16-ch AI Coding
- 1 Bay. Up to 16TB for Each HDD Storage Capacity

Summary: Dahua Technology XVR1B16-I/T. Product colour: Black, Maximum video resolution: 1920 x 1080 pixels, Video compression formats: H.264, H.264+, H.265, H.265+. Video input channels: 16 channels. Ethernet interface type: Fast Ethernet, Supported network protocols: HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS;..., Number of users: 128 user(s). HDD interface: SATA, SATA II, SATA III, Maximum HDD capacity: 6 TB. DC voltage: 12 V, Power consumption (typical): 10 W | Vendor Homepage:

<https://www.dahuasecurity.com/products/hdcvi-products/hdcvi-recorders/cooper-i-series/xvr1b16-i/t> |

Audio input: 1 | Audio output: 1 | BNC input ports: 16 | HDMI ports quantity: 1 | USB 2.0 ports quantity: 2 | VGA (D-Sub) output ports: 1 | Video input channels: 16 | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Ethernet LAN (RJ-45) ports: 1 | Number of users: 128 | Supported network protocols: HTTP; HTTPS; TCP/IP; IPv4; IPv6; RTSP; UDP; NTP; DHCP; DNS; SMTP; UPnP; IP Filter; FTP; DDNS; SNMP; Alarm Server; P2P; Auto Registration; IP Search (Supports IP camera, DVR, NVS, etc.) | HDD interface: SATA/SATA II/SATA III | Maximum HDD capacity: 6000 | Number of HDDs supported: 1 | Analog signal format system: NTSC/PAL | Audio formats supported: G.711/G.711u/PCM | Audio system: 2-way | Bit rate: 4096 | Dual stream support: Yes | Graphical user interface (GUI): Yes | Internal: No | Maximum video resolution: 1920 x 1080 | Operating system installed: Embedded LINUX | Playback resolutions supported: 1920 x 1080, 1280 x 1024, 1280 x 720 | Product colour: Black | PTZ control: Yes | Rack capacity: 1U | Video capturing speed: 30 | Video compression formats: H.264/H.264+/H.265/H.265+ | Video motion detection: Yes | Video streaming: Yes | Built-in processor: Yes | DC voltage: 12 | Power consumption (typical): 10 | Depth: 231.4 | Height: 47.6 | Weight: 890 | Width: 260 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -10 - 45 | Storage relative humidity (H-H): 0 - 90 | Storage temperature (T-T): -20 - 70 | Model: XVR1B16-I/T | Units per Shipping Box: 1 | Unit Calculated Volume: 0.008554 | Unit Calculated Weight: 1.49

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950