

NET CAMERA 4MP DOME/IPC-HDBW2449E-S-IL-0280B DAHUA

NET CAMERA 4MP DOME/IPC- HDBW2449E-S- IL-0280B DAHUA



Model: IPC-HDBW2449E-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172514202

Product Code: 406677

R4,181

- 4-MP 1/2.9" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2688 × 1520) @20 fps, and supports 2560 × 1440@25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED and warm light , the max. IR illumination distance is 30 m and the max. warm light distance is 30 m
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection
- Supports max. 256 G Micro SD card; built in Mic
- 12 VDC/PoE power supply, easy for installation
- IP67, IK10 protection
- SMD Plus

Summary: Dahua Technology WizSense IPC-HDBW2449E-S-IL-0280B. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Dome. Angle of rotation: 355°, Lens viewing angle, horizontal: 101°, Lens viewing angle, vertical: 54°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.9 mm (1 / 2.9"). Detect distance: 63.6 m, Observe distance: 25.4 m, Recognize distance: 12.7 m | Vendor Homepage: <https://www.dahuasecurity.com/ro/products/All-Products/Network-Cameras/WizSense-Series/2-Series/Smart-Dual-Illuminators/IPC-HDBW2449E-S-IL> | Form factor: Dome | Mounting type: Ceiling/Wall/Pole | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired | Placement supported: Outdoor | Day/night mode: Yes | Dynamic range: 120 | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Minimum illumination: 0 | Angle of rotation: 355 | Lens viewing angle, horizontal: 101 | Lens viewing angle, vertical: 54 | Lens viewing angle, diagonal: 120 | Tilt angle range: 0 - 65 | Pan range: 0 - 355 | White balance: Auto/Manual/Natural/Outdoor/Regional custom/Street lamp | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Optical sensor size: 1/2.9 | Progressive scan: Yes | Sensor type: CMOS | Detect distance: 63.6 | Observe distance: 25.4 | Recognize distance: 12.7 | Identify distance: 6.4 | Closest focusing distance: 1.1 | Fixed focal length: 2.8 | Night vision: Yes | Night vision distance: 30 | LED type: IR/White | Maximum resolution: 2688 x 1520 | Total megapixels: 4 | Video compression formats: H.264/H.264B/H.264H/H.265/M-JPEG | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2560 x 1440/2688 x 1520/352 x 240/352 x 288/640 x 480 (VGA)/704 x 480/704 x 576 | Frame rate: 30 | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Gain control type: Auto/Manual | Back Light Compensation (BLC): Yes | Bit rate: H.264: 32 kbps-6144 kbps; H.265: 12 kbps-6144 kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Highlight Compensation (HLC): Yes | Region of Interest (ROI) encoding: Yes | Built-in microphone: Yes | Voice codecs: G.711a/G.711Mu/G.726/PCM | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Networking standards: IEEE 802.3af | Supported network protocols: IPv4; IPv6; HTTP; TCP; UDP; ARP;

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; P2P | Wi-Fi: No | Bluetooth: No | Number of users: 6 | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | ROM capacity: 128 | RAM capacity: 128 | Ethernet LAN (RJ-45) ports: 1 | Mirror: Yes | Video motion detection: Yes | Web browser: Yes | Management software: Smart PSS Lite; DSS; DMSS; DoLynk Care | Power source type: DC,PoE | Power consumption (typical): 2.4 | Power consumption (max): 7.9 | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Height: 81 | Diameter: 109.9 | Weight: 350 | Package weight: 500 | Number of cameras: 1 | Unit Calculated Weight: 0.54 | Product Net Weight: 0.35 | Unit Calculated Volume: 0.002769 | Units per Shipping Box: 20 | Shipping Box Height: 26 | Name: NET CAMERA 4MP DOME/IPC-HDBW2449E-S-IL-0280B DAHUA | Model: IPC-HDBW2449E-S-IL-0280B

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950