

Dahua Technology Mobile Camera DH-IPC-HDBW1430DE-SW security camera Dome IP se



Dahua Technology Mobile Camera DH-IPC- HDBW1430DE- SW security camera Dome IP security camera Indoor & outdoor 2560 x 1440 pixels Ceiling

Model: IPC-HDBW1430DE-SW-0280B

Manufacturer: DAHUA

EAN: 6923172539984

Product Code: 406824

R3,698

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- 4-MP 1/3" CMOS image sensor, low luminance, and high definition image
- Outputs max. 4 MP (2560 × 1440)@20 fps, and max. supports 3 MP (2304 × 1296)@25/30 fps
- H.265 codec, high compression rate, ultra-low bit rate
- Built-in IR LED
- SMART H.264 +/H.265+, flexible coding, applicable to various band width and storage environments
- DWDR, 3D NR, BLC, digital watermarking, applicable to various monitoring scenes
- Abnormality detection: Motion detection, video tampering, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, SMD (human)
- Supports single antenna 2.4G Wi-Fi that covers a range of up to 80 m in an open area
- Supports max. 256 G Micro SD card
- 12 VDC power supply
- IP67, IK10 protection

Summary: Dahua Technology Mobile Camera DH-IPC-HDBW1430DE-SW. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired & Wireless. Mounting type: Ceiling, Product colour: White, Form factor: Dome. Angle of rotation: 355°, Lens viewing angle, horizontal: 90°, Tilt angle range: 0 - 75°. Sensor type: CMOS, Optical sensor size: 25.4 / 3 mm (1 / 3"). Detect distance: 68 m, Observe distance: 27.2 m, Recognize distance: 13.6 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/Network-Cameras/Wireless-Series/Wi-Fi-Series/4MP/IPC-HDBW1430DE-SW> | Form factor: Dome | Mounting type: Ceiling | Product colour: White | Housing material: Metal | International Protection (IP) code: IP67 | IK code: IK10 | Type: IP security camera | Connectivity technology: Wired & Wireless | Placement supported: Indoor & outdoor | Wide Dynamic Range (WDR): Yes | Day/night mode: Yes | Remote viewing: Yes | Antenna type: External | Antennas quantity: 1 | Certification: CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU; CE-RED: Radio Equipment Directive 2014/53/EU; FCC: 47 CFR FCC Part 15, Subpart B; FCC ID: FCC PART 15C | Angle of rotation: 355 | Lens viewing angle, horizontal: 90 | Tilt angle range: 0 - 75 | Pan range: 0 - 355 | Camera shutter type: Electronic | Camera shutter speed: 1/3 - 1/100000 | Adjustment shutter speed: Auto/Manual | Number of sensors: 1 | Optical sensor size: 1/3 | Progressive scan: Yes | Digital Wide Dynamic Range (DWDR) (panoramic camera): Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 68 | Observe distance: 27.2 | Recognize distance: 13.6 | Auto focus: Yes | Identify distance: 6.8 | Maximum aperture number: 2 | Fixed focal length (thermal module): 2.8 | Night vision: Yes | Night vision distance: 30 | LED type: IR | Number of illumination LEDs: 3 | Maximum resolution: 2560 x 1440 | Total megapixels:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

4 | Video formats supported: H.264/H.264B/H.265 | Video compression formats: H.264+/H.264H/H.265+ | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/2304 x 1296/2560 x 1440 | Supported video modes: 1080p/720p | Video recording: Yes | Frame rate: 30 | Video intelligence analytic: Yes | Video streaming: Yes | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Back Light Compensation (BLC): Yes | Bit rate: 3 Kbps - 20480 Kbps | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Digital Wide Dynamic Range (DWDR): Yes | Highlight Compensation (HLC): Yes | Smart IR: Yes | Audio system: 1-way | Audio system full duplex: Yes | Audio codecs: G.711a; G.711Mu; PCM; G.726; G.723 | Ethernet LAN: Yes | Ethernet interface type: Fast Ethernet | Wi-Fi: Yes | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n) | Bluetooth: No | Number of users: 6 | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Internal memory: 64 | ROM capacity: 16 | Ethernet LAN (RJ-45) ports: 1 | Detection distance: 80 | Intelligent Video Surveillance (IVS) system features: Intrusion | Mirror: Yes | Web browser: Yes | Power source type: DC,PoE | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Mobile operating systems supported: Android/iOS | Height: 88.7 | Diameter: 110.7 | Weight: 414 | Package weight: 592 | Number of cameras: 1 | Unit Calculated Weight: 0.639 | Product Net Weight: 0.414 | Unit Calculated Volume: 0.002537 | Units per Shipping Box: 1 | Unit Width: 12.5 | Shipping Box Height: 14.5 | Unit Depth: 14 | Unit Height: 14.5 | Name: NET CAMERA 4MP IR DOME WIFI/IPC-HDBW1430DE-SW-0280B DAHUA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950