



Power Supply

LIAN LI

SP0750G.W SFX

PC 100 - 240 V

750 W

G9P.SP0750G.W000.EU

Model: G9P.SP0750G.W000.EU

Manufacturer: LIAN LI

EAN: 4718466018434

Product Code: 407034

R3,071

Блок живлення SFX Lian Li 80 PLUS Gold 750W White (G9P.SP0750G.W000.EU)

PERFORMANCE SFX FORM FACTOR POWER SUPPLY

The SP V2 Gold is a stylish high-performance PSU that perfectly fits small-form-factor PCs while supporting power-hungry components.

AVAILABLE IN TWO COLORS & TWO WATTAGES

Choose the fully modular SFX PSU in black or white, with 850W or 750W options to perfectly match your build.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

COMPACT SIZE, BIG PERFORMANCE

Measuring 125 × 100 × 63.5 mm, this compact PSU saves valuable space inside the builds without compromising on power delivery.

80 PLUS GOLD CERTIFICATE

With 80 PLUS Gold certification, the SP V2 Gold delivers over 90% efficiency at 50% system load under 115V AC input conditions, ensuring high energy efficiency with stable power delivery and minimal energy loss.

ATX 3.1 READY WITH 12V-2×6 CONNECTOR

The SP V2 Gold features a next-gen 12V-2×6 power connector compliant with the latest ATX 3.1 specification, providing direct support for PCIe 5.0 graphics cards and addressing the growing power demands of modern systems.

LIAN LI CUSTOM 12V-2×6 POWER CABLE

LIAN LI's in-house developed 12V-2×6 power cable features a custom-molded design combined with alloy copper soldered terminals to deliver superior stability and efficient power delivery. Built to meet the demanding needs of high-end graphics cards, this cable ensures safer, more durable connections for your cutting-edge system.

Each cable is engineered for ease of use, with dual-color connector housings for intuitive installation, reinforced soldering for improved reliability, and a 20.5mm connector width optimized to prevent interference during GPU mounting.

SP V2 Gold COMPOSITION

Aesthetic - Aluminum Housing

Silent - Zero RPM mode

Powerful - 850 Watts / 750 Watts

Perfect Size - SFX Form

Practical - Fully Modular Design

Longevity - Japanese Electrolytic Capacitors

FDB FAN FOR QUIET COOLING

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

The SP V2 Gold utilizes a 92mm FDB fan to deliver efficient cooling with low noise. Even under sustained high workloads, it maintains stable performance while ensuring silent operation.

JAPANESE ELECTROLYTIC CAPACITORS

Premium Japanese electrolytic capacitors provide great durability and long-term reliability, as well as offer the highest stability.

ENHANCED DURABILITY WITH EMBOSSED CABLE DESIGN

The embossed cable design enhances both durability and flexibility, ensuring long-lasting performance even under frequent use. Its unique textured surface helps reduce tangling and knotting, delivering a smoother installation experience and cleaner cable management.

SUFFICIENT PROTECTION

Features OCP (Over Current Protection), OVP (Over Voltage Protection), SCP (Short Circuit Protection), OPP (Over Power Protection), UVP (Under Voltage Protection), OTP (Over Temperature Protection) and inrush current limiter that make the PSU operating in stable condition.

TEN YEARS WARRANTY

LIAN LI now offers a 10-year warranty for the SP V2 Gold2 series. With ongoing quality improvements and rigorous testing, the warranty has been extended to 10 years — reflecting our confidence in the reliability and performance of our high-quality SFX power supply units.

- Compact 125 × 100 × 63.5 mm SFX size for space-limited builds
- 80 PLUS Gold certified with 90%+ efficiency at 50% load (115V)
- ATX 3.1 & PCIe 5.0 ready with native 12V-2×6 GPU support
- Exclusive 12V-2×6 cable design prevents GPU clearance issues
- 92 mm FDB fan with ZERO RPM mode for silent operation
- Fully modular design with anti-tangle embossed cables
- Offering comprehensive protection mechanisms, including OCP, OVP, SCP, OPP, UVP, OTP

Summary: Lian Li SP0750G.W. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50/60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 35 cm, SATA power cable length: 350 mm. Purpose: PC, Power supply unit (PSU) form factor: SFX, 80 PLUS certification: 80 PLUS Gold. Product colour: White, Cooling type: Active, Fan diameter: 9.2 cm.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Width: 125 mm, Depth: 100 mm, Height: 63.5 mm | Vendor Homepage: <https://lian-li.com/product/sp-v2> | Total power: 750 | AC input voltage: 100 - 240 | AC input frequency: 50/60 | Input current: 5 - 10 | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 100 | Combined power (+12V): 744 | Combined power (+5V): 100 | Combined power (-12V): 3.6 | Combined power (+5Vsb): 15 | Max output current (+3.3V): 20 | Max output current (+12V): 62 | Max output current (+5V): 20 | Max output current (-12V): 0.3 | Max output current (+5Vsb): 3 | Efficiency: 90 | Power protection features: No load operation/Over current/Over power/Over voltage/Short circuit/Surge & inrush protection (SIP)/Under temperature/Under voltage | Motherboard power connector: 20+4 pin ATX | Motherboard power cable length: 350 | Number of SATA power connectors: 7 | SATA power cable length: 350 | Peripheral (Molex) power connectors (4-pin): 1 | EPS power connector (8-pin): Yes | PCI Express power connectors (6+2 pin): 2 | PCI Express power connectors (8-pin): 1 | PCI Express power cable length: 400 | CPU power connector (4+4 pin): Yes | CPU power cable length: 600 | Cabling type: Fully-Modular | 80 PLUS certification: 80 PLUS Gold | Purpose: PC | Power supply unit (PSU) form factor: SFX | ATX version: 3.1 | Noise level: 32.5 | Bearing technology: FDB | Product colour: White | Cooling type: Active | Fan diameter: 92 | Number of fans: 1 | Fan speed: 0 - 3000 | On/off switch: Yes | Operating temperature (T-T): 0 - 40 | Width: 125 | Depth: 100 | Height: 63.5 | Unit Calculated Weight: 1.87 | Product Net Weight: 1.7 | Unit Calculated Volume: 0.006102 | Units per Shipping Box: 10 | Unit Width: 19 | Units per Pallet: 0 | Shipping Box Height: 27 | Unit Depth: 25 | Unit Height: 11 | Name: CASE PSU SFX 750W WHITE/G9P.SP0750G.W000.EU LIAN LI | Model name: SP0750G.W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950