


# Dahua Technology HAC-HDW1549X-IL-A-PRO Turret IP security camera Outdoor 2880 x 1620 pixels Ceiling/Wall/Pole

Model: HAC-HDW1549X-IL-A-PRO-0280B-DIP

Manufacturer: DAHUA

EAN: 6937552409446

Product Code: 407122

## R2,852

- High-Quality Imaging with 5MP 16:9 Resolution
- Smart Dual Light: Built-in IR and LED Lights with 3 Illumination Modes Supported
- WizColor Technology: Exceptional Image Quality in Low-Light Conditions
- Built-In Dual Mic : Enhances Video Assistance with Dual Mic Technology
- Smart Light+ : Clear Details with Advanced LED Processing Technology

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- 3DNR & DWDR & Super Adapt Ensures Clear Details in Strong Backlight Conditions
- Effortless Signal Selection with DIP Switch
- Time-saving Installation with Quick-to-install Structure
- IP67 Ratings for Protection Against Harsh Environments

Summary: Dahua Technology HAC-HDW1549X-IL-A-PRO. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.0001 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 111°. Sensor type: CMOS. Detect distance: 63.8 m, Observe distance: 25.5 m, Recognize distance: 12.8 m | Vendor Homepage: https://www.dahuasecurity.com/products/hdcvi-products/hdcvi-cameras/lite-series/5mp/wizcolor/hac-hdw1549x-il-a-pro | Tipas: IP apsaugos kamera | Ryšio technologija: Vielinis | Talpinimas palaikomas: Lauke | Maksimalus veikimo nuotolis: 50 | Išplėstinis dinaminis diapazonas (WDR): Taip | Dienos / nakties režimas: Taip | Sertifikavimas: CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; | Forma: Bokštelis | Montavimo tipas: Ant lubų / sienos / stulpo | Produkto spalva: Balta | Korpuso medžiaga: Metalas/Plastikas | Tarptautinės apsaugos (IP) kodas: IP67 | Minimalus apšviestumas: 0.0001 | Sukimosi kampas: 360 | Objektyvo vaizdo kampas, horizontalus: 111 | Objektyvo vaizdo kampas, vertikalus: 58.5 | Objektyvo vaizdo kampas, įstrižainė: 136.3 | Posvyrio kampo intervalas: 0 - 90 | Viso diapozonas: 0 - 360 | Baltos spalvos balansas: Automatinis | Kameros užrakto greitis: 1/30 - 1/100000 | Progresyvus nuskaitymas: Taip | Jutiklio tipas: CMOS | Aptikties atstumas: 63.8 | Stebėjimo atstumas: 25.5 | Atpažinimo atstumas: 12.8 | Židinio nuotolis: 2.8 | Fiksuotas fokusavimas: Taip | Identifikavimo atstumas: 6.4 | Maksimalus apertūros skaičius: 1 | Mažiausias fokusavimo atstumas: 1.4 | Naktinis matymas: Taip | Naktinio matymo atstumas: 50 | LED tipas: IR | Maksimali rezoliucija: 2880 x 1620 | Iš viso megapikselių: 5 | Palaikomos grafikos rezoliucijos: 2560 x 1440/2880 x 1620/2960 x 1665/960 x 480/960 x 576 | Kadrų sparta: 25 | Analoginio signalo formato sistema: NTSC/PAL | Triukšmo mažinimas: Taip | Triukšmo sumažinimo technologija: 3D triukšmo mažinimas | Valdymo sustiprinimo tipas: Automatinis | „Smart IR“ įtaisas: Taip | Privatumo maskavimas: Taip | Signalo ir triukšmo santykis (SNR): 65 | Įmontuotas mikrofonas: Taip | Mikrofonų kiekis: 2 | Integruotas kietasis diskas: Ne | BNC išvesties prievadai: 1 | Vaizdo judesio detekcija: Taip | Veidrodis: Taip | Maitinimo šaltinio tipas: DC | Galios suvartojimas (maks.): 6.1 | DC išeigos įtampa: 12 | Darbo temperatūros diapazonas (TT): -40 - 60 | Sandėliavimo temperatūros norma (T-T): -40 - 60 | Darbo santykinės drėgmės diapazonas: 0 - 95 | Sandėliavimo santykinis drėgmės diapazonas: 0 - 95 | Aukštis: 102.2 | Skersmuo: 109.9 | Svoris: 330 | Atitikties sertifikatai: CE | Paketo svoris: 450 | Pakuotės tipas: „Box“ | Fotoaparatų skaičius: 1 | Lęšio montavimo sąsaja: M12 | Bruto svoris: 0.46 | Neto svoris: 0.33 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 13.1 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 11.5 | Vieneto gylis: 13.1 | Vieneto aukštis: 11.5 | Name: CAMERA HDCVI 5MP EYEBALL/HDW1549X-IL-APRO0280BDIP DAHUA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950