



**Dahua
Technology
HAC-HDW1549X-
IL-A-PRO Turret
IP security
camera Outdoor
2880 x 1620
pixels
Ceiling/Wall/Pole**

Model: HAC-HDW1549X-IL-A-PRO-0280B-DIP

Manufacturer: DAHUA

EAN: 6937552409446

Product Code: 407122

R2,852

- High-Quality Imaging with 5MP 16:9 Resolution
- Smart Dual Light: Built-in IR and LED Lights with 3 Illumination Modes Supported
- WizColor Technology: Exceptional Image Quality in Low-Light Conditions
- Built-In Dual Mic : Enhances Video Assistance with Dual Mic Technology
- Smart Light+ : Clear Details with Advanced LED Processing Technology

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- 3DNR & DWDR & Super Adapt Ensures Clear Details in Strong Backlight Conditions
- Effortless Signal Selection with DIP Switch
- Time-saving Installation with Quick-to-install Structure
- IP67 Ratings for Protection Against Harsh Environments

Summary: Dahua Technology HAC-HDW1549X-IL-A-PRO. Type: IP security camera, Placement supported: Outdoor, Connectivity technology: Wired. Mounting type: Ceiling/Wall/Pole, Product colour: White, Form factor: Turret. Minimum illumination: 0.0001 lx, Angle of rotation: 360°, Lens viewing angle, horizontal: 111°. Sensor type: CMOS. Detect distance: 63.8 m, Observe distance: 25.5 m, Recognize distance: 12.8 m | Vendor Homepage: <https://www.dahuasecurity.com/products/hdcvi-products/hdcvi-cameras/lite-series/5mp/wizcolor/hac-hdw1549x-il-a-pro> | Certification: CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035; | Connectivity technology: Wired | Day/night mode: Yes | Maximum operating distance: 50 | Placement supported: Outdoor | Type: IP security camera | Wide Dynamic Range (WDR): Yes | Form factor: Turret | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Mounting type: Ceiling/Wall/Pole | Product colour: White | Angle of rotation: 360 | Camera shutter speed: 1/30 - 1/100000 | Lens viewing angle, diagonal: 136.3 | Lens viewing angle, horizontal: 111 | Lens viewing angle, vertical: 58.5 | Minimum illumination: 0.0001 | Pan range: 0 - 360 | Tilt angle range: 0 - 90 | White balance: Auto | Progressive scan: Yes | Sensor type: CMOS | Closest focusing distance: 1.4 | Detect distance: 63.8 | Fixed focus: Yes | Focal length range: 2.8 | Identify distance: 6.4 | Maximum aperture number: 1 | Observe distance: 25.5 | Recognize distance: 12.8 | LED type: IR | Night vision: Yes | Night vision distance: 50 | Analog signal format system: NTSC/PAL | Frame rate: 25 | Gain control type: Auto | Maximum resolution: 2880 x 1620 | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Privacy masking: Yes | Smart IR: Yes | Supported graphics resolutions: 2560 x 1440/2880 x 1620/2960 x 1665/960 x 480/960 x 576 | Total megapixels: 5 | Built-in microphone: Yes | Number of microphones: 2 | Signal-to-Noise Ratio (SNR): 65 | Built-in HDD: No | BNC output ports: 1 | Mirror: Yes | Video motion detection: Yes | DC output voltage: 12 | Power consumption (max): 6.1 | Power source type: DC | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): -40 - 60 | Storage relative humidity (H-H): 0 - 95 | Storage temperature (T-T): -40 - 60 | Diameter: 109.9 | Height: 102.2 | Weight: 330 | Compliance certificates: CE | Package type: Box | Package weight: 450 | Number of cameras: 1 | Lens mount interface: M12 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.001974 | Unit Calculated Weight: 0.46

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950