



CAMERA HDCVI 2MP IR EYEBALL/HAC- HDW1231TMQ- A-0280B DAHUA



Model: HAC-HDW1231TMQ-A-0280B

Manufacturer: DAHUA

EAN: 6923172506887

Product Code: 407359

R2,389

- Max 30 fps@1080p
- Starlight, 130 dB true WDR, 3D NR
- 3.6 mm fixed lens (2.8 mm, 6 mm optional)
- CVI/CVBS/AHD/TVI switchable
- Super Adapt
- Built-in mic
- Max. IR length 60 m, Smart IR
- IP67, DC 12 V
- Quick-to-install saves installation time

Summary: Dahua Technology Lite HAC-HDW1231TMQ-A. Type: CCTV security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired. Mounting type: Ceiling/wall, Product

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

colour: White, Form factor: Dome. Minimum illumination: 0.002 lx, Angle of rotation: 360°, Tilt angle range: 0 - 90°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.8 mm (1 / 2.8"). Detect distance: 82.8 m, Observe distance: 33.1 m, Recognize distance: 16.6 m | Vendor Homepage: <https://www.dahuasecurity.com/products/All-Products/HDCVI-Cameras/Lite-Series/1080P/Starlight/HAC-HDW1231TMQ-A> | Type: CCTV security camera | Connectivity technology: Wired | Placement supported: Indoor & outdoor | Wide Dynamic Range (WDR): Yes | Certification: CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1) | Form factor: Dome | Mounting type: Ceiling/wall | Product colour: White | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Camera pan control: Yes | Camera tilt control: Yes | Minimum illumination: 0.002 | Angle of rotation: 360 | Tilt angle range: 0 - 90 | Pan range: 0 - 360 | White balance: Auto/Manual | Camera shutter type: Electronic | Camera shutter speed: PAL: 1/25 s-1/100,000 s/PAL: 1/25 s-1/100,000 s | Adjustment shutter speed: Auto/Manual | Optical sensor size: 1/2.8 | Progressive scan: Yes | Sensor type: CMOS | Number of lenses: 1 | Detect distance: 82.8 | Observe distance: 33.1 | Recognize distance: 16.6 | Focal length range: 2.8 - 3.6 - 6 | Identify distance: 8.3 | Maximum aperture number: 1.6 | Night vision: Yes | Night vision distance: 60 | LED type: IR | Number of illumination LEDs: 2 | Maximum resolution: 1920 x 1080 | Total megapixels: 2 | Supported graphics resolutions: 1280 x 720 (HD 720)/1920 x 1080 (HD 1080) | Supported video modes: 1080p/720p | Frame rate: 30 | Analog signal format system: PAL | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Back Light Compensation (BLC): Yes | Highlight Compensation (HLC): Yes | Privacy masking: Yes | Smart IR: Yes | Audio input channels: 1.0 | Signal-to-Noise Ratio (SNR): 65 | Ethernet LAN: No | Wi-Fi: No | Bluetooth: No | Built-in HDD: No | BNC output ports: 1 | Mirror: Yes | Power source type: DC | DC output voltage: 12 | Operating temperature (T-T): -40 - 60 | Storage temperature (T-T): -40 - 60 | Operating relative humidity (H-H): 0 - 95 | Storage relative humidity (H-H): 0 - 95 | Height: 99.1 | Diameter: 121.9 | Weight: 420 | Package weight: 620 | Number of cameras: 1 | Unit Calculated Weight: 0.62 | Product Net Weight: 0.17 | Unit Calculated Volume: 0.002835 | Units per Shipping Box: 1 | Shipping Box Height: 13.5 | Name: CAMERA HDCVI 2MP IR EYEBALL/HAC-HDW1231TMQ-A-0280B DAHUA

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950