



Power Supply XILENCE 750 Watts Efficiency 80 PLUS GOLD PFC Active XN330

Model: XN330

Manufacturer: XILENCE

EAN: 4044953503320

Product Code: 407362

R2,377

XN330 | XP750R12

The Gaming GOLD Series is a PC power supply series with a fixed cable harness, as well as a 750W ARGB variant. The noble design with its black powder coating, the 120mm silent, black or transparent fan and the fan grille emphasizes the valuable character of this series.

The maximum voltage stability and the six integrated safety circuits ensure safe operation even in heated workflows or gaming sessions. The power supplies are suitable for the highest demands in gaming, multi-media application and streaming areas and have low power consumption during these intensive phases. The power supplies achieve the 80+ GOLD requirements.

- **Whisper-Quiet Cooling: Large 120mm fan***

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Excellent Airflow Design for Improved Heat Dissipation
- With the Following Safety Equipment:
- OVP (Overvoltage Protection)
- UVP (Undervoltage Protection)
- SCP (Short Circuit Protection)
- OLP (Overload Protection)
- OTP (Over Temperature Protection)
- OCP (Overcurrent Protection)
- Low Standby Power Consumption

Summary: Xilence Performance A+ XN330 | XP750R12. Total power: 750 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20-pin ATX, Motherboard power cable length: 5.5 cm, Cabling type: Non-Modular. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Certification: 80PLUS certification | Vendor Homepage: <https://www.xilence.net/en/power-supplies/231> | Total power: 750 | AC input voltage: 200 - 240 | AC input frequency: 50 | Input current: 6.3 | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 66 | Combined power (+5V): 100 | Combined power (-12V): 6 | Combined power (+5Vsb): 15 | Max output current (+12V): 62.5 | Power protection features: Over power/Over voltage/Short circuit/Under voltage | Motherboard power connector: 20-pin ATX | Motherboard power cable length: 55 | Number of SATA power connectors: 6 | PCI Express power connectors (6+2 pin): 3 | CPU power connector (4+4 pin): Yes | ATX power connector (20+4 pin): Yes | Floppy disk drive connector: No | PCI Express connector: Yes | Cabling type: Non-Modular | 80 PLUS certification: 80 PLUS Gold | Supported motherboard form factors: ATX | Purpose: PC | Power supply unit (PSU) form factor: ATX | ATX version: 2.52 | Silent mode: Yes | Bearing technology: HDB | Product colour: Black | Cooling type: Active | Fan diameter: 120 | Number of fans: 1 | Fan location: Top | On/off switch: Yes | Certification: 80PLUS certification | Width: 198 | Depth: 247 | Height: 98 | Weight: 2300 | Unit Calculated Weight: 2.21 | Product Net Weight: 2 | Unit Calculated Volume: 0.006569 | Units per Shipping Box: 5 | Unit Width: 10 | Units per Pallet: 0 | Shipping Box Height: 23 | Unit Depth: 26 | Unit Height: 20 | Name: CASE PSU ATX2.52 750W/XP750R12 XN330 XILENCE | Model name: XN330 | XP750R12

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950