



WRL CAMERA 2MP IR BULLET WIFI/F2C-PV 2.8MM DAHUA



Model: F2C-PV2.8MM

Manufacturer: DAHUA

EAN: 6939554914508

Product Code: 407881

R1,540 ~~R1,940~~

The Bullet Series, which is under the Dahua Wireless series, are cameras that are not only easy to install and operate, but also perform outstandingly and are cost-effective. They capture sharp, detailed images of scenes in high definition and offer powerful functions, such as AI human detection, to accurately trigger alarms. Information is also synchronously sent to your phone to keep you up-to-date. With its IP67 rating, these cameras are able to withstand harsh environments, making them highly suitable for use in small and medium-sized settings such as small-sized retail stores.

Summary: Dahua Technology F2C-PV. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wired & Wireless. Mounting type: Ceiling/wall, Product colour: White, Form factor: Bullet. Horizontal field of view (thermal module): 98°, Lens viewing angle, horizontal: 55°, Lens viewing angle, diagonal: 115°. Sensor type: CMOS, Optical sensor size: 25.4 / 3 mm (1 / 3"). Fixed focal length: 2.8 mm | Vendor Homepage:

<https://www.dahuasecurity.com/products/All-Products/Network-Cameras/Wireless-Series/NEW->

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Channel/Outdoor-Camera/Bullet-Series/F2C-PV | Connectivity technology: Wired & Wireless | Placement supported: Indoor & outdoor | Type: IP security camera | Form factor: Bullet | Housing material: Metal/Plastic | International Protection (IP) code: IP67 | Mounting type: Ceiling/wall | Product colour: White | Weatherproof: Yes | Camera shutter speed: 1/3 - 1/100000 | Camera shutter type: Electronic | Horizontal field of view (thermal module): 98 | Lens viewing angle, diagonal: 115 | Lens viewing angle, horizontal: 55 | Optical sensor size: 1/3 | Sensor type: CMOS | Fixed focal length: 2.8 | Maximum aperture number: 1.6 | LED type: IR/White | Night vision: Yes | Night vision distance: 30 | Number of illumination LEDs: 2 | Digital Wide Dynamic Range (DWDR): Yes | Frame rate: 30 | Maximum resolution: 1920 x 1080 | Smart IR: Yes | Supported graphics resolutions: 1280 x 720 (HD 720)/1280 x 960/1920 x 1080 (HD 1080)/640 x 480 (VGA) | Total megapixels: 2 | Video formats supported: H.264/H.264B/H.265 | Audio formats supported: G.711/G.726 | Built-in microphone: Yes | Built-in speaker(s): Yes | Voice codecs: G.711a/G.711Mu | Ethernet interface type: Fast Ethernet | Ethernet LAN: Yes | Wi-Fi: Yes | Wi-Fi standards: 802.11b/802.11g/Wi-Fi 4 (802.11n) | Built-in HDD: No | Card reader integrated: Yes | Compatible memory cards: MicroSD (TransFlash) | Maximum memory card size: 256 | Ethernet LAN (RJ-45) ports: 1 | Video motion detection: Yes | Management software: Smart PSS; DSS; DMSS | Smartphone/tablet remote support: Yes | Power consumption (max): 6.5 | Power consumption (typical): 2 | Power source type: DC | Operating temperature (T-T): - 40 - 60 | Mobile operating systems supported: Android/iOS | Depth: 78.4 | Height: 97.2 | Weight: 266.5 | Width: 131 | Number of cameras: 1 | Model: F2C-PV 2.8MM | Units per Shipping Box: 30 | Unit Calculated Volume: 0.002818 | Unit Calculated Weight: 0.583

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950