



**HDD SEAGATE**  
**6TB SAS 256 MB**  
**7200 rpm MTBF**  
**2000000 hours**  
**ST6000NM020B**



Model: ST6000NM020B

Manufacturer: SEAGATE

EAN: 8719706022125

Product Code: 40852

---

**R8,184** ~~R8,625~~

---

**Purpose-built for enterprise applications and workloads**

**Trusted. Efficient. Versatile**

For everything Enterprise storage, there's Exos E — the safest and most powerful way to traverse the datasphere and harness its full potential. Always on and always working, the Exos E series of hard drives is loaded with advanced options for optimal performance, reliability, security and user-definable storage management. Built on generations of industry-defining innovation, Exos E is designed to work and perform consistently in enterprise-class workloads.

**Exos 7E10**

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Specifically designed to address the needs of storing unstructured data cost-effectively.

Summary: Seagate Enterprise ST6000NM020B. HDD capacity: 6 TB, HDD speed: 7200 RPM, Storage drive buffer size: 256 MB, HDD size: 3.5", Interface: SAS | Vendor Homepage:

<https://www.seagate.com/gb/en/products/enterprise-drives/exos-e/7e10/> | 24/7 operation: Yes | Average latency: 4.16 | Component for: Disk array | HDD capacity: 6000 | HDD interface transfer rate: 12 | HDD size: 3.5 | HDD speed: 7200 | Interface: SAS | Mean time between failures (MTBF): 2000000 | Rotational Vibration (RV) sensors: Yes | Storage drive buffer size: 256 | Type: HDD | Uncorrectable Bit Error Rate (UBER): 1 per 10<sup>15</sup> bits read | Operating voltage: 5 / 12 | Power consumption (idle): 6.59 | Power consumption (typical): 10.8 | Non-operating shock: 300 | Non-operating vibration: 5 | Operating shock: 70 | Operating temperature (T-T): 5 - 60 | Depth: 147 | Height: 26.11 | Weight: 650 | Width: 101.85 | Harmonized System (HS) code: 84717050 | Units per Shipping Box: 20 | Unit Calculated Volume: 0.00165 | Unit Calculated Weight: 0.7

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950