



IP CAMERA DAHUA IPC- HFW1639TC-A- IL-0280B-S6

Model: IPC-HFW1639TC-A-IL-0280B-S6

Manufacturer: DAHUA

EAN: 6923172563354

Product Code: 418791

R2,025

Ambient temperature: -40°C ~ +60°C | RAM: 256 MB | Number of Privacy masking areas: 4 | Bitrate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Lens: Permanent | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Operating temperature: -40°C ~ +60°C | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | ROM: 128 MB | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Form factor: Bullet | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 352 x 288 | Weight: 440 g | Supported graphics resolutions: 3840 x 2160 | Type: IP security camera | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Supported graphics resolutions: 640 x 480 (VGA) | Connectivity technology: Wired | Power consumption (max): 4 W | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3200 x 1800 |

Maximum resolution: 3200 x 1800 pixels | Supported graphics resolutions: 2880 x 1620 | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

consumption (typical): 2.9 W | Web-based management: Yes | Operating relative humidity (H-H): 0 - 95% | Width: 173 mm | Product colour: Black | Power source type: DC, PoE | Built-in microphone: Yes | Signal-to-Noise Ratio (SNR): 56 dB | Supported network protocols: IPv4 IPv6 HTTP TCP UDP ARP RTP RTSP RTCP RTMP SMTP FTP SFTP DHCP DNS DDNS NTP Multicast ICMP IGMP | Built-in HDD: No | LED type: 1 IR LED + white light LED | Camera shutter speed: 1/3 - 1/100000 s | Ethernet interface type: Fast Ethernet | Voice codecs: G.711a | Voice codecs: G.726 | Voice codecs: G.711Mu | Housing material: Metal | Frame rate: 25 / 30 fps | Adjustment shutter speed: Auto/Manual | Progressive scan: Yes | Depth: 70 mm | Number of cameras: 1 | Height: 70 mm | Total megapixels: 6 MP | Wi-Fi: No | International Protection (IP) code: IP67 | Wide Dynamic Range (WDR): Yes | Night vision distance: 30 m | Voice codecs: PCM | Video compression formats: M-JPEG | Video compression formats: H.265 | Video compression formats: H.264+ | Video streaming: Yes | Active tampering alarm: Yes | Mounting type: Ceiling | Sensor type: CMOS | Web browser: Yes | Viewing angle: 110° | Video compression formats: H.265+ | Video motion detection: Yes | Regulatory Approvals: CE-LVD: EN62368-1 CE-EMC: Dyrektywa Kompatybilności Elektromagnetycznej 2014/30/EU | Audio detection: Yes | Observe distance: 30 m | Ethernet : One 10/100Mbps RJ45 port | Noise reduction technology: 3D NR | Night vision: Yes | Placement supported: External / Internal

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950