



IP CAMERA DAHUA IPC- HDW2849TM-S- IL-0280B

Model: IPC-HDW2849TM-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172581549

Product Code: 418794

R3,397

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-04-10 | Connectivity technology: Wired | Weight: 480 g | Bluetooth: No | Height: 99.1 mm | Audio formats supported: PCM | Audio formats supported: G.711a | Sensor type: CMOS | Operating relative humidity (H-H): 0 - 95% | Progressive scan: Yes | Back Light Compensation (BLC): Yes | Power consumption (max): 5 W | Supported graphics resolutions: 1280 x 720 (HD 720) | Power source type: DC, PoE | Tilt angle range: 0 - 78° | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | International Protection (IP) code: IP67 | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Ethernet interface type: Fast Ethernet | Highlight Compensation (HLC): Yes | Video compression formats: H.264+ | Supported graphics resolutions: 352 x 288 | ROM capacity: 128 MB | Diameter: 12.2 cm | Signal-to-Noise Ratio (SNR): 56 dB | White balance: Outdoor | Closest focusing distance: 1.5 m | Total megapixels: 8 MP | Internal memory: 256 MB | Mounting type: Ceiling | Product colour: White | Storage temperature (T-T): -40 - 60 °C | Number of cameras: 1 | Audio formats supported: G.726 | Lens viewing angle, diagonal: 132° | Noise reduction: Yes | Video compression formats: H.265 | Supported graphics resolutions: 3840 x

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

2160 | Adjustment shutter speed: Auto/Manual | Gain control type: Auto/Manual | DC output voltage: 12 | Video compression formats: H.264B | Mobile operating systems supported: Android | Type: IP security camera | White balance: Natural | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Lens viewing angle, vertical: 58° | White balance: Auto | Bit rate: H.264: 32 kbps–8192 kbps H.265: 12 kbps–8192 kbps | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 3072 x 2048 | Frame rate: 30 fps | Number of lenses: 1 | Region of Interest (ROI) encoding: Yes | Maximum aperture number: 1.6 | Noise reduction technology: 3D noise reduction | Minimum illumination: 0.008 lx | Web-based management: Yes | Power consumption (Power over Ethernet (PoE)): 5.9 W | White balance: Street lamp | Supported graphics resolutions: 2880 x 1620 | Housing material: Metal, Plastic | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Wide Dynamic Range (WDR): 120 dB | Video streaming: Yes | Number of sensors: 1 | Camera shutter speed: 1/3 - 1/100000 s | Maximum resolution: 3840 x 2160 pixels | Wi-Fi: No | Video compression formats: H.264H | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Placement supported: External / Internal | White balance: Manual | Web browser: Yes | Lens type: Fixed focal length lens | Video compression formats: H.265+ | Lens viewing angle, horizontal: 111° | Pan range: 0 - 360° | Night vision distance: 30 m | Focal length range: 2.8 mm | Number of users: 20 user(s) | Built-in microphone: Yes | Night vision: Yes | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.3af | Video compression formats: H.264 | Audio formats supported: G.711Mu | Built-in HDD: No | Video compression formats: M-JPEG | Number of illumination LEDs: 2 | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Operating temperature (T-T): -40 - 55 °C | Mirror function: Yes | Mobile operating systems supported: iOS | LED type: IR / White light LED | Form factor: Dome | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Warnings: The product contains electronic components do not dispose of with the normal household waste.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950